



Backing Ring ANSI steel insert injection  
moulded Flange connection PP-FRP grey

The torques nm[NM] specified in the technical catalogue are to be used as maximum values.

Size	Code	Detail	Weight	da(OD) mm	d mm	d2 mm	d3 mm
20	11.013.0020.11	20 - 1/2" - MOP 16 bar	0.210	20	95	16	28
25	11.013.0025.11	25 - 3/4" - MOP 16 bar	0.230	25	102	16	34
32	11.013.0032.11	32 - 1" - MOP 16 bar	0.380	32	114	16	42
40	11.013.0040.11	40 - 1 1/4" - MOP 16 bar	0.560	40	130	16	51
50	11.013.0050.11	50 - 1 1/2" - MOP 16 bar	0.548	50	133	16	62
63	11.013.0063.11	63 - 2" - MOP 16 bar	0.810	63	162	20	78
75	11.013.0075.11	75 - 2 1/2" - MOP 16 bar	1.092	75	184	20	92
90	11.013.0090.11	90 - 3" - MOP 16 bar	1.060	90	194	20	111
110/125	11.013.0110.11	110/125 - 4" - MOP 16 bar	1.541	110	229	20	133
140	11.013.0140.11	140 - 5" - MOP 16 bar	2.250	140	258	22	158
160	11.013.0160.11	160 - 6" - MOP 16 bar	2.357	160	283	22	178
200/225	11.013.0200.11	200/225 - 8" - MOP 16 bar	3.893	200	345	22	236
250/280	11.013.0250.11	250/280 - 10" - MOP 16 bar	6.089	250	412	25	288
315	11.013.0315.11	315 - 12" - MOP 16 bar	12.940	315	487	25	338