



Bend 90° short spigot electrically  
conductive injection moulded Butt-  
welding PE 100-el black

Size	Code	Detail	Weight	da(OD) mm	s mm	r mm	z mm
180	28.001.0180.17	180X10,7 SDR17 ISO S-8	2.020	180	10,7	180	200
200	28.001.0200.17	200X11,9 SDR17 ISO S-8	2.700	200	11,9	200	220
225	28.001.0225.17	225X13,4 SDR17 ISO S-8	3.680	225	13,4	225	245
250	28.001.0250.17	250X14,8 SDR17 ISO S-8	6.380	250	14,8	265	285
315	28.001.0315.17	315X18,7 SDR17 ISO S-8	12.040	315	18,7	300	340
180	28.001.0180.11	180X16,4 SDR11 ISO S-5	2.980	180	16,4	180	200
200	28.001.0200.11	200X18,2 SDR11 ISO S-5	4.140	200	18,2	200	220
225	28.001.0225.11	225X20,5 SDR11 ISO S-5	5.840	225	20,5	225	243
250	28.001.0250.11	250X22,7 SDR11 ISO S-5	8.780	250	22,7	265	290
315	28.001.0315.11	315X28,6 SDR11 ISO S-5	15.500	315	28,6	300	340