



Reducer concentric short spigot
electrically conductive injection moulded
Butt-welding PE 100-el black

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
160/110	28.007.1611.17	160/110 SDR17 ISO S-8	0.311	160	110	9,5	6,6	83	13	13
225/160	28.007.2216.17	225/160 SDR17 ISO S-8	0.800	225	160	13,4	9,5	90	15	12
315/225	28.007.3122.17	315/225 SDR17 ISO S-8	2.080	315	225	18,7	13,4	130	25	20
63/16	28.007.6316.11	63/16 SDR11 ISO S-5	0.048	63	16	5,8	1,8	97	10	8
110/63	28.007.1163.11	110/63 SDR11 ISO S-5	0.140	110	63	10	5,8	62	9	6
160/110	28.007.1611.11	160/110 SDR11 ISO S-5	0.455	160	110	14,6	10	83	13	13
225/160	28.007.2216.11	225/160 SDR11 ISO S-5	1.070	225	160	20,5	14,6	90	15	12
315/225	28.007.3122.11	315/225 SDR11 ISO S-5	2.920	315	225	28,6	20,5	130	25	20