



E-Coupler injection moulded Electro-fusion PPR grey

Size	Code	Detail	Weight	da(OD) mm	L mm	d mm	d1 mm
20	11.173.0020.11	20 SDR 11 - 7,4	0.035	20	75	30	36,5
25	11.173.0025.11	25 SDR 11 - 7,4	0.043	25	81	35,5	39,5
32	11.173.0032.11	32 SDR 11 - 7,4	0.060	32	89	43,5	42,5
40	11.173.0040.11	40 SDR 11 - 7,4	0.096	40	99	54,5	47,3
50	11.173.0050.11	50 SDR 11 - 7,4	0.150	50	111	67,5	53
63	11.173.0063.11	63 SDR 17,6 - 7,4	0.256	63	126	83,5	59
75	11.173.0075.11	75 SDR 17,6 - 7,4	0.350	75	141	97	65,5
90	11.173.0090.11	90 SDR 17,6 - 7,4	0.494	90	142	114	73
110	11.173.0110.11	110 SDR 17,6 - 7,4	0.745	110	152	139	83
125	11.173.0125.11	125 SDR 17,6 - 11	1.245	125	171	161	90,5
140	11.173.0140.11	140 SDR 17,6 - 7,4	1.653	140	182	180	98
160	11.173.0160.11	160 SDR 17,6 - 11	1.841	160	181	200	108,5
180	11.173.0180.11	180 SDR 17,6 - 11	2.470	180	202	222	119
200	11.173.0200.11	200 SDR 17,6 - 11	3.390	200	218	247	131
225	11.173.0225.11	225 SDR 17,6 - 11	4.300	225	233	277	144
250	11.173.0250.11	250 SDR 17,6 - 11	5.000	250	243	310	159
280	11.173.0280.11	280 SDR 17,6 - 11	6.272	280	254	348	174
315	11.173.0315.11	315 SDR 17,6 - 11	7.760	315	262	393	201
355	11.173.0355.11	355 SDR 17,6 - 11	11.000	355	284	439	209