



Tee reduced long spigot injection
moulded Butt + E-fusion-welding PPR
grey

Size	Code	Detail	Weight	da(OD) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
63/50	11.065.6350.17	63/50 SDR17 ISO S-8	0.208	63	3,8	3	103	220	63	56
75/50	11.065.7550.17	75/50 SDR17 ISO S-8	0.406	75	4,5	3	110	265	75	56
75/63	11.065.7563.17	75/63 SDR17 ISO S-8	0.415	75	4,5	3,8	117	260	72	63
90/63	11.065.9063.17	90/63 SDR17 ISO S-8	0.591	90	5,4	3,8	138,5	275	81	64
90/75	11.065.9075.17	90/75 SDR17 ISO S-8	0.600	90	5,4	4,5	138	278	77	71
110/63	11.065.1163.17	110/63 SDR17 ISO S-8	0.957	110	6,6	3,8	159	315	87	65
110/75	11.065.1175.17	110/75 SDR17 ISO S-8	0.850	110	6,6	4,5	151	315	85	70
110/90	11.065.1190.17	110/90 SDR17 ISO S-8	0.915	110	6,6	5,4	156	320	85	82



Size	Code	Detail	Weight	da(OD) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
125/63	11.065.1263.17	125/63 SDR17 ISO S-8	1.380	125	7,4	3,8	170	354	110	70
125/90	11.065.1290.17	125/90 SDR17 ISO S-8	1.300	125	7,4	5,4	172	351	110	85
125/110	11.065.1211.17	125/110 SDR17 ISO S-8	1.235	125	7,4	6,6	170	340	90	83
160/63	11.065.1663.17	160/63 SDR17 ISO S-8	1.920	160	9,5	3,8	175	351	100	67
160/75	11.065.1675.17	160/75 SDR17 ISO S-8	1.905	160	9,5	4,5	179	348	101	76
160/90	11.065.1690.17	160/90 SDR17 ISO S-8	1.990	160	9,5	5,4	182	352	101	80
160/110	11.065.1611.17	160/110 SDR17 ISO S-8	2.360	160	9,5	6,6	202	400	100	85
180/90	11.065.1890.17	180/90 SDR17 ISO S-8	3.100	180	10,7	5,4	202	427	138	97
200/63	11.065.2063.17	200/63 SDR17 ISO S-8	4.963	200	11,9	3,8	226	560	135	81
200/90	11.065.2090.17	200/90 SDR17 ISO S-8	5.124	200	11,9	5,4	229	560	134	95
200/110	11.065.2011.17	200/110 SDR17 ISO S-8	5.220	200	11,9	6,6	245	560	136	105
200/125	11.065.2012.17	200/125 SDR17 ISO S-8	5.260	200	11,9	7,4	240	550	134	110



Size	Code	Detail	Weight	da(OD) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
200/160	11.065.2016.17	200/160 SDR17 ISO S-8	6.154	200	11,9	9,5	275	564	137	118
225/75	11.065.2275.17	225/75 SDR17 ISO S-8	4.900	225	13,4	4,5	226	456	124	75
225/90	11.065.2290.17	225/90 SDR17 ISO S-8	5.000	225	13,4	5,4	226	458	124	81
225/110	11.065.2211.17	225/110 SDR17 ISO S-8	4.960	225	13,4	6,6	226	458	124	85
225/160	11.065.2216.17	225/160 SDR17 ISO S-8	6.260	225	13,4	9,5	250	505	122,5	100
225/180	11.065.2218.17	225/180 SDR17 ISO S-8	7.680	225	13,4	10,7	280	558	135	135
250/110	11.065.2511.17	250/110 SDR17 ISO S-8	9.980	250	14,8	6,6	247	632	152	87
250/160	11.065.2516.17	250/160 SDR17 ISO S-8	10.540	250	14,8	9,5	272	636	151	101
250/200	11.065.2520.17	250/200 SDR17 ISO S-8	11.060	250	14,8	11,9	294	630	148	118,5
315/110	11.065.3111.17	315/110 SDR17 ISO S-8	11.400	315	18,7	6,6	292	555	170	102
315/160	11.065.3116.17	315/160 SDR17 ISO S-8	12.560	315	18,7	9,5	315	585	170	120
315/200	11.065.3120.17	315/200 SDR17 ISO S-8	15.440	315	18,7	11,9	331	650	170	129,5



Size	Code	Detail	Weight	da(OD) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
315/225	11.065.3122.17	315/225 SDR17 ISO S-8	15.400	315	18,7	13,4	335	650	170	145
315/250	11.065.3125.17	315/250 SDR17 ISO S-8	16.200	315	18,7	14,8	340	680	170	150
400/225	11.065.4022.17	400/225 SDR17 ISO S-8	36.840	400	23,7	13,4	375	940	191	130
63/25	11.065.6325.11	63/25 SDR11 ISO S-5	0.190	63	5,8	2,3	85	170	65	43
63/32	11.065.6332.11	63/32 SDR11 ISO S-5	0.290	63	5,8	2,9	103	220	63	50
63/40	11.065.6340.11	63/40 SDR11 ISO S-5	0.290	63	5,8	3,7	96	229	66	51
63/50	11.065.6350.11	63/50 SDR11 ISO S-5	0.292	63	5,8	4,6	103	220	63	57
75/32	11.065.7532.11	75/32 SDR11 ISO S-5	0.490	75	6,8	2,9	107,5	265	75,5	47
75/50	11.065.7550.11	75/50 SDR11 ISO S-5	0.530	75	6,8	4,6	110	265	75	56
75/63	11.065.7563.11	75/63 SDR11 ISO S-5	0.537	75	6,8	5,8	119	260	72	63
90/63	11.065.9063.11	90/63 SDR11 ISO S-5	0.739	90	8,2	5,8	138,5	275	81	65
90/75	11.065.9075.11	90/75 SDR11 ISO S-5	0.796	90	8,2	6,8	140	278	77	71



Size	Code	Detail	Weight	da(OD) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
110/63	11.065.1163.11	110/63 SDR11 ISO S-5	1.240	110	10	5,8	159	315	87	65
110/75	11.065.1175.11	110/75 SDR11 ISO S-5	1.180	110	10	6,8	151	315	85	70
110/90	11.065.1190.11	110/90 SDR11 ISO S-5	1.261	110	10	8,2	156	317	85	81
125/90	11.065.1290.11	125/90 SDR11 ISO S-5	1.640	125	11,4	8,2	170	340	112	92
125/110	11.065.1211.11	125/110 SDR11 ISO S-5	1.850	125	11,4	10	170	340	90	83
160/63	11.065.1663.11	160/63 SDR11 ISO S-5	2.690	160	14,6	5,8	169	357,5	101	65,5
160/75	11.065.1675.11	160/75 SDR11 ISO S-5	2.620	160	14,6	6,8	179	358	101	73
160/90	11.065.1690.11	160/90 SDR11 ISO S-5	2.640	160	14,6	8,2	186	358	101	82
160/110	11.065.1611.11	160/110 SDR11 ISO S-5	2.870	160	14,6	10	190	359	100	85
180/90	11.065.1890.11	180/90 SDR11 ISO S-5	3.590	180	16,4	8,2	196	372	106	81
180/110	11.065.1811.11	180/110 SDR11 ISO S-5	3.630	180	16,4	10	202	373	107	84
200/63	11.065.2063.11	200/63 SDR11 ISO S-5	6.940	200	18,2	5,8	226	560	135	83



Size	Code	Detail	Weight	da(OD) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
200/90	11.065.2090.11	200/90 SDR11 ISO S-5	6.860	200	18,2	8,2	230	560	137	92
200/110	11.065.2011.11	200/110 SDR11 ISO S-5	6.980	200	18,2	10	245	560	136	105
200/125	11.065.2012.11	200/125 SDR11 ISO S-5	6.920	200	18,2	11,4	240	560	134	110
200/160	11.065.2016.11	200/160 SDR11 ISO S-5	8.340	200	18,2	14,6	275	564	137	118
225/75	11.065.2275.11	225/75 SDR11 ISO S-5	6.620	225	20,5	6,8	226	455	124	77
225/90	11.065.2290.11	225/90 SDR11 ISO S-5	6.660	225	20,5	8,2	226	456	124	81
225/110	11.065.2211.11	225/110 SDR11 ISO S-5	6.660	225	20,5	10	226	456	124	85
225/160	11.065.2216.11	225/160 SDR11 ISO S-5	8.220	225	20,5	14,6	250	498	120	100
225/180	11.065.2218.11	225/180 SDR11 ISO S-5	9.800	225	20,5	16,4	277	558	135	135
250/110	11.065.2511.11	250/110 SDR11 ISO S-5	12.460	250	22,7	10	247	632	152	87
250/160	11.065.2516.11	250/160 SDR11 ISO S-5	12.960	250	22,7	14,6	272	634	152	101
250/200	11.065.2520.11	250/200 SDR11 ISO S-5	14.060	250	22,7	18,2	294	630	152	118,5



Size	Code	Detail	Weight	da(OD) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
315/110	11.065.3111.11	315/110 SDR11 ISO S-5	15.400	315	28,6	10	289	555	170	102
315/160	11.065.3116.11	315/160 SDR11 ISO S-5	16.790	315	28,6	14,6	310	585	170	120
315/200	11.065.3120.11	315/200 SDR11 ISO S-5	20.640	315	28,6	18,2	331	650	170	129,5
315/225	11.065.3122.11	315/225 SDR11 ISO S-5	20.580	315	28,6	20,5	331	650	170	145
315/250	11.065.3125.11	315/250 SDR11 ISO S-5	21.840	315	28,6	22,7	340	680	170	150