



Tee long spigot injection moulded Butt +  
E-fusion-welding PPR grey

Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
20	11.066.0020.11	20X1,9 SDR11 ISO S-5	0.020	20	1,9	57	109	37
25	11.066.0025.11	25X2,3 SDR11 ISO S-5	0.030	25	2,3	59	117	40
32	11.066.0032.11	32X2,9 SDR11 ISO S-5	0.060	32	2,9	72	144	45
40	11.066.0040.11	40X3,7 SDR11 ISO S-5	0.111	40	3,7	84	168	51
50	11.066.0050.11	50X4,6 SDR11 ISO S-5	0.190	50	4,6	97	192	58
63	11.066.0063.11	63X5,8 SDR11 ISO S-5	0.360	63	5,8	115	229	66
75	11.066.0075.11	75X6,8 SDR11 ISO S-5	0.613	75	6,8	131	264	71
90	11.066.0090.11	90X8,2 SDR11 ISO S-5	0.954	90	8,2	146	293	82
110	11.066.0110.11	110X10,0 SDR11 ISO S-5	1.500	110	10	162	320	88
125	11.066.0125.11	125X11,4 SDR11 ISO S-5	2.140	125	11,4	175	356	93,5
140	11.066.0140.11	140X12,7 SDR11 ISO S-5	2.765	140	12,7	190	380	98



Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
160	11.066.0160.11	160X14,6 SDR11 ISO S-5	3.820	160	14,6	208	410	105
180	11.066.0180.11	180X16,4 SDR11 ISO S-5	5.390	180	16,4	230	464	108
200	11.066.0200.11	200X18,2 SDR11 ISO S-5	7.740	200	18,2	250	500	116
225	11.066.0225.11	225X20,5 SDR11 ISO S-5	10.600	225	20,5	275	552	125,5
250	11.066.0250.11	250X22,7 SDR11 ISO S-5	14.880	250	22,7	315	630	148
280	11.066.0280.11	280X25,4 SDR11 ISO S-5	20.320	280	25,4	352	704	161
315	11.066.0315.11	315X28,6 SDR11 ISO S-5	27.800	315	28,6	380	760	170