



Reducer concentric injection moulded
Socket-welding PPR grey

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	L mm
25/20	11.057.2520.07	25/20 - MOP 20 bar	0.011	25	20	39
32/20	11.057.3220.07	32/20 - MOP 20 bar	0.015	32	20	44,5
32/25	11.057.3225.07	32/25 - MOP 20 bar	0.018	32	25	45
40/20	11.057.4020.07	40/20 - MOP 20 bar	0.022	40	20	50
40/25	11.057.4025.07	40/25 - MOP 20 bar	0.025	40	25	50
40/32	11.057.4032.07	40/32 - MOP 20 bar	0.027	40	32	50
50/20	11.057.5020.07	50/20 - MOP 20 bar	0.033	50	20	55,5
50/25	11.057.5025.07	50/25 - MOP 20 bar	0.034	50	25	55
50/32	11.057.5032.07	50/32 - MOP 20 bar	0.037	50	32	55
50/40	11.057.5040.07	50/40 - MOP 20 bar	0.043	50	40	54,5
63/25	11.057.6325.07	63/25 - MOP 20 bar	0.054	63	25	65
63/32	11.057.6332.07	63/32 - MOP 20 bar	0.059	63	32	65
63/40	11.057.6340.07	63/40 - MOP 20 bar	0.065	63	40	64,5
63/50	11.057.6350.07	63/50 - MOP 20 bar	0.076	63	50	65
75/63	11.057.7563.07	75/63 - MOP 16 bar	0.105	75	63	64
90/63	11.057.9063.07	90/63 - MOP 16 bar	0.160	90	63	87,5
90/75	11.057.9075.07	90/75 - MOP 16 bar	0.184	90	75	86,6
110/63	11.057.1163.07	110/63 - MOP 10 bar	0.252	110	63	90
110/90	11.057.1190.07	110/90 - MOP 10 bar	0.303	110	90	88