



Stub Flange JIS short spigot injection moulded Butt-welding PPR grey

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
20	11.012.2020.11	20X1,9 SDR11 ISO S-5	0.016	20	1,9	52	30	27	45	7
25	11.012.2025.11	25X2,3 SDR11 ISO S-5	0.031	25	2,3	52	25	33	58	9
32	11.012.2032.11	32X2,9 SDR11 ISO S-5	0.040	32	2,9	50	25	40	68	10
40	11.012.2040.11	40X3,7 SDR11 ISO S-5	0.061	40	3,7	52	24	50	78	11
50	11.012.2050.11	50X4,6 SDR11 ISO S-5	0.075	50	4,6	53	22	61	84	12
63	11.012.2063.11	63X5,8 SDR11 ISO S-5	0.115	63	5,8	50	20	75	99	14
75	11.012.2075.11	75X6,8 SDR11 ISO S-5	0.180	75	6,8	50,5	18	89	119	16
90	11.012.2090.11	90X8,2 SDR11 ISO S-5	0.285	90	8,2	82	40	105	129	17



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	11.012.2110.11	110X10,0 SDR11 ISO S-5	0.410	110	10	82	38	125	154	18
125	11.012.2125.11	125X11,4 SDR11 ISO S-5	0.509	125	11,4	82	38	132	154	25
140	11.012.2140.11	140X12,7 SDR11 ISO S-5	0.740	140	12,7	92	37	155	185	25
160	11.012.2160.11	160X14,6 SDR11 ISO S-5	0.940	160	14,6	92	38	175	212	25
200	11.012.2200.11	200X18,2 SDR11 ISO S-5	1.935	200	18,2	114	40	232	268	32
225	11.012.2225.11	225X20,5 SDR11 ISO S-5	1.900	225	20,5	113	52	235	265	32
250	11.012.2250.11	250X22,7 SDR11 ISO S-5	3.260	250	22,7	130	58	285	320	35
280	11.012.2280.11	280X25,4 SDR11 ISO S-5	3.021	280	25,4	128	66	288	320	35
315	11.012.2315.11	315X28,6 SDR11 ISO S-5	4.460	315	28,6	136	65	335	370	35