



Tee reduced short spigot injection moulded Butt-welding PPR grey

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
140/63	11.016.1463.17	140/63 SDR17 ISO S-8	1.311	140	63	8,3	3,8	120	302	86	32
140/75	11.016.1475.17	140/75 SDR17 ISO S-8	1.400	140	75	8,3	4,5	130	300	86	35
140/90	11.016.1490.17	140/90 SDR17 ISO S-8	1.320	140	90	8,3	5,4	130	304	86	42
140/110	11.016.1411.17	140/110 SDR17 ISO S-8	1.640	140	110	8,3	6,6	139	300	50	47
160/125	11.016.1612.17	160/125 SDR17 ISO S-8	2.040	160	125	9,5	7,4	150	315	62	48
180/63	11.016.1863.17	180/63 SDR17 ISO S-8	2.060	180	63	10,7	3,8	139	358	130	32
180/75	11.016.1875.17	180/75 SDR17 ISO S-8	2.100	180	75	10,7	4,5	140	360	120	31
180/110	11.016.1811.17	180/110 SDR17 ISO S-8	2.160	180	110	10,7	6,6	160	365	106	48
180/125	11.016.1812.17	180/125 SDR17 ISO S-8	2.240	180	125	10,7	7,4	156	365	96	52



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
225/125	11.016.2212.17	225/125 SDR17 ISO S-8	4.190	225	125	13,4	7,4	180	455	140	45
63/32	11.016.6332.11	63/32 SDR11 ISO S-5	0.182	63	32	5,8	2,9	70	130	18	18
90/32	11.016.9032.11	90/32 SDR11 ISO S-5	0.562	90	32	8,2	2,9	85	213	57	23
90/50	11.016.9050.11	90/50 SDR11 ISO S-5	0.563	90	50	8,2	4,6	90	213	57	27
110/32	11.016.1132.11	110/32 SDR11 ISO S-5	0.910	110	32	10	2,9	94	244	70	23
110/50	11.016.1150.11	110/50 SDR11 ISO S-5	0.941	110	50	10	4,6	103	244	70	27
125/63	11.016.1263.11	125/63 SDR11 ISO S-5	1.360	125	63	11,4	5,8	112	280	76	31
140/63	11.016.1463.11	140/63 SDR11 ISO S-5	1.800	140	63	12,7	5,8	120	302	87	32
140/75	11.016.1475.11	140/75 SDR11 ISO S-5	1.920	140	75	12,7	6,8	130	305	54	35
140/90	11.016.1490.11	140/90 SDR11 ISO S-5	1.840	140	90	12,7	8,2	130	305	88	42
140/110	11.016.1411.11	140/110 SDR11 ISO S-5	2.180	140	110	12,7	10	141	305	54	47
160/125	11.016.1612.11	160/125 SDR11 ISO S-5	2.720	160	125	14,6	11,4	158	335	62	52
180/63	11.016.1863.11	180/63 SDR11 ISO S-5	3.040	180	63	16,4	5,8	144	367	134	32



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
180/75	11.016.1875.11	180/75 SDR11 ISO S-5	3.100	180	75	16,4	6,8	148	366	123	31
180/125	11.016.1812.11	180/125 SDR11 ISO S-5	3.280	180	125	16,4	11,4	166	366	100	52
225/125	11.016.2212.11	225/125 SDR11 ISO S-5	6.120	225	125	20,5	11,4	178	456	143	45