



Bend 30° segmented/inside bead
removed derating factor 0.8 Butt-welding
PPH grey

Size	Code	Detail	Weight	da(OD) mm	s mm	z mm
560	12.329.0560.41	560X13,7 SDR41 ISO S-20	18.800	560	13,7	425
630	12.329.0630.41	630X15,4 SDR41 ISO S-20	24.200	630	15,4	434
710	12.329.0710.41	710X17,4 SDR41 ISO S-20	35.900	710	17,4	495
800	12.329.0800.41	800X19,6 SDR41 ISO S-20	56.000	800	19,6	507
900	12.329.0900.41	900X22,0 SDR41 ISO S-20	72.100	900	22	521
1000	12.329.1000.41	1000X24,5 SDR41 ISO S-20	91.000	1.000	24,5	634
1200	12.329.1200.41	1200X29,4 SDR41 ISO S-20	136.000	1.200	29,4	661
560	12.329.0560.33	560X17,2 SDR33 ISO S-16	23.300	560	17,2	425
630	12.329.0630.33	630X19,3 SDR33 ISO S-16	30.100	630	19,3	434
710	12.329.0710.33	710X21,8 SDR33 ISO S-16	44.700	710	21,8	495
800	12.329.0800.33	800X24,5 SDR33 ISO S-16	69.400	800	24,5	507
900	12.329.0900.33	900X27,6 SDR33 ISO S-16	90.000	900	27,6	500
1000	12.329.1000.33	1000X30,6 SDR33 ISO S-16	113.000	1.000	30,6	634
1200	12.329.1200.33	1200X36,7 SDR33 ISO S-16	169.000	1.200	36,7	661
560	12.329.0560.26	560X21,4 SDR26 ISO S-12,5	28.700	560	21,4	425
630	12.329.0630.26	630X24,1 SDR26 ISO S-12,5	37.300	630	24,1	434
710	12.329.0710.26	710X27,2 SDR26 ISO S-12,5	55.200	710	27,2	495
800	12.329.0800.26	800X30,6 SDR26 ISO S-12,5	86.000	800	30,6	507
900	12.329.0900.26	900X34,4 SDR26 ISO S-12,5	93.200	900	34,4	521



Size	Code	Detail	Weight	da(OD) mm	s mm	z mm
560	12.329.0560.17	560X31,7 SDR17,6 ISO S-8,3	41.700	560	31,7	425
630	12.329.0630.17	630X35,7 SDR17,6 ISO S-8,3	54.100	630	35,7	434
710	12.329.0710.17	710X40,2 SDR17,6 ISO S-8,3	79.900	710	40,2	495
800	12.329.0800.17	800X45,3 SDR17,6 ISO S-8,3	104.000	800	47,4	507