



Bend 90° short spigot flame retardant & el-conduct. injection moulded Butt-welding PPs-el black

Size	Code	Detail	Weight	da(OD) mm	s mm	r mm	z mm
110	19.001.0110.33	110X3,4 SDR33 MOP<1,5bar	0.321	110	3,4	110	120
160	19.001.0160.33	160X4,9 SDR33 MOP<1,5bar	0.965	160	4,9	155	180
200	19.001.0200.33	200X6,2 SDR33 MOP<1,5bar	1.760	200	6,2	200	220
225	19.001.0225.33	225X6,9 SDR33 MOP<1,5bar	2.440	225	6,9	225	245
250	19.001.0250.33	250X7,7 SDR33 MOP<1,5bar	3.680	250	7,7	265	290
315	19.001.0315.33	315X9,7 SDR33 MOP<1,5bar	6.420	315	9,7	300	340
110	19.001.0110.17	110X6,6 SDR17 MOP<3,5bar	0.540	110	6,6	110	123
160	19.001.0160.17	160X9,5 SDR17 MOP<3,5bar	1.661	160	9,5	155	180
200	19.001.0200.17	200X11,9 SDR17 MOP<3,5bar	3.090	200	11,9	200	220
32	19.001.0032.11	32X2,9 SDR11 MOP<6bar	0.026	32	2,9	32	43
50	19.001.0050.11	50X4,6 SDR11 MOP<6bar	0.093	50	4,6	50	60
63	19.001.0063.11	63X5,8 SDR11 MOP<6bar	0.150	63	5,8	63	70
75	19.001.0075.11	75X6,8 SDR11 MOP<6bar	0.260	75	6,8	75	85



Size	Code	Detail	Weight	da(OD) mm	s mm	r mm	z mm
90	19.001.0090.11	90X8,2 SDR11 MOP<6bar	0.440	90	8,2	90	100
110	19.001.0110.11	110X10,0 SDR11 MOP<6bar	0.735	110	10	110	124