



Tee short spigot flame retardant & el-conduct. injection moulded Butt-welding PPS-el black

Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
110	19.006.0110.33	110X3,4 SDR33 MOP<1,5bar	0.622	110	3,4	109	223	33
160	19.006.0160.33	160X4,9 SDR33 MOP<1,5bar	2.220	160	4,9	173	346	57
200	19.006.0200.33	200X6,2 SDR33 MOP<1,5bar	4.100	200	6,2	205	410	57
225	19.006.0225.33	225X6,9 SDR33 MOP<1,5bar	5.680	225	6,9	222	448	57
250	19.006.0250.33	250X7,7 SDR33 MOP<1,5bar	8.180	250	7,7	237	475	70
315	19.006.0315.33	315X9,7 SDR33 MOP<1,5bar	12.700	315	9,7	277	558	80
110	19.006.0110.17	110X6,6 SDR17 MOP<3,5bar	1.160	110	6,6	121	251	50,5
160	19.006.0160.17	160X9,5 SDR17 MOP<3,5bar	3.200	160	9,5	173	346	57
200	19.006.0200.17	200X11,9 SDR17 MOP<3,5bar	5.900	200	11,9	202,5	405	57
32	19.006.0032.11	32X2,9 SDR11 MOP<6bar	0.046	32	2,9	45	90	20,5
50	19.006.0050.11	50X4,6 SDR11 MOP<6bar	0.157	50	4,6	60	120	23



Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
63	19.006.0063.11	63X5,8 SDR11 MOP<6bar	0.290	63	5,8	72	144	25
75	19.006.0075.11	75X6,8 SDR11 MOP<6bar	0.500	75	6,8	75	152	15
90	19.006.0090.11	90X8,2 SDR11 MOP<6bar	0.905	90	8,2	105	213	38
110	19.006.0110.11	110X10,0 SDR11 MOP<6bar	1.540	110	10	122	253	51