



Reducer concentric short spigot flame retardant & el-conduct. injection moulded
Butt-welding PPs-el black

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
160/110	19.007.1611.33	160/110 SDR33 MOP <1,5bar	0.210	160	110	4,9	3,4	83	13	13
225/160	19.007.2216.33	225/160 SDR33 MOP <1,5bar	0.512	225	160	6,9	4,9	94	18	14
315/225	19.007.3122.33	315/225 SDR33 MOP <1,5bar	1.510	315	225	9,7	6,9	134	25	20
160/110	19.007.1611.17	160/110 SDR17 MOP <3,5bar	0.358	160	110	9,5	6,6	83	13	13
225/160	19.007.2216.17	225/160 SDR17 MOP <3,5bar	0.834	225	160	13,4	9,5	94	18	14
63/16	19.007.6316.11	63/16 SDR11 MOP <6bar	0.054	63	16	5,8	1,8	97	10	8



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
75/32	19.007.7532.11	75/32 SDR11 MOP <6bar	0.079	75	32	6,8	2,9	71	10	9
110/63	19.007.1163.11	110/63 SDR11 MOP <6bar	0.187	110	63	10	5,8	62	9	6