



Stub Flange DIN short spigot flame retardant & el-conduct. injection moulded  
Butt-welding PPs-el black

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	19.012.0110.33	110X3,4 SDR33 MOP<1,5bar	0.375	110	3,4	80	31	125	158	18
160	19.012.0160.33	160X4,9 SDR33 MOP<1,5bar	0.684	160	4,9	80	28,5	175	212	18
200	19.012.0200.33	200X6,2 SDR33 MOP<1,5bar	1.340	200	6,2	113	53	232	268	18
225	19.012.0225.33	225X6,9 SDR33 MOP<1,5bar	1.030	225	6,9	113	65	235	268	18
250	19.012.0250.33	250X7,7 SDR33 MOP<1,5bar	2.260	250	7,7	132	70	285	320	20
315	19.012.0315.33	315X9,7 SDR33 MOP<1,5bar	2.780	315	9,7	136	68	335	370	20
110	19.012.0110.17	110X6,6 SDR17 MOP<3,5bar	0.460	110	6,6	80	34	125	158	18
160	19.012.0160.17	160X9,5 SDR17 MOP<3,5bar	0.900	160	9,5	92	42	175	212	18



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
200	19.012.0200.17	200X11,9 SDR17 MOP<3,5bar	1.880	200	11,9	110	46	232	268	24
32	19.012.0032.11	32X2,9 SDR11 MOP<6bar	0.050	32	2,9	50	25	40	68	10
50	19.012.0050.11	50X4,6 SDR11 MOP<6bar	0.112	50	4,6	53	22	61	88	12
63	19.012.0063.11	63X5,8 SDR11 MOP<6bar	0.155	63	5,8	50	20	75	102	14
75	19.012.0075.11	75X6,8 SDR11 MOP<6bar	0.242	75	6,8	50,5	18	89	122	16
90	19.012.0090.11	90X8,2 SDR11 MOP<6bar	0.430	90	8,2	82	40	105	138	17
110	19.012.0110.11	110X10,0 SDR11 MOP<6bar	0.570	110	10	82	38	125	158	18