



Stub Flange DIN short spigot flame retardant injection moulded Butt-welding PPs grey

Dim. 90 - 160 SDR 11 Discontinued products. Backing Rings please see Accessories.

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	17.012.0110.33	110X3,4 SDR33 ISO S-16	0.280	110	3,4	80	31	125	158	18
160	17.012.0160.33	160X4,9 SDR33 ISO S-16	0.516	160	4,9	80	28,5	175	212	18
180	17.012.0180.33	180X5,5 SDR33 ISO S-16	0.424	180	5,5	95	55	183	212	18
200	17.012.0200.33	200X6,2 SDR33 ISO S-16	1.120	200	6,2	113	53	232	268	18
225	17.012.0225.33	225X6,9 SDR33 ISO S-16	0.860	225	6,9	113	65	235	268	18
250	17.012.0250.33	250X7,7 SDR33 ISO S-16	1.780	250	7,7	132	70	285	320	20
280	17.012.0280.33	280X8,6 SDR33 ISO S-16	1.195	280	8,6	128	62	288	320	20



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
315	17.012.0315.33	315X9,7 SDR33 ISO S-16	2.160	315	9,7	136	68	335	370	20
355	17.012.0355.33	355X10,9 SDR33 ISO S-16	2.980	355	10,9	150	75	373	430	23
400	17.012.0400.33	400X12,3 SDR33 ISO S-16	4.180	400	12,3	155	75	427	482	26
500	17.012.0500.33	500X15,3 SDR33 ISO S-16	7.110	500	15,3	120	37	530	585	33
20	17.012.0020.11	20X1,9 SDR11 ISO S-5	0.016	20	1,9	52	30	27	45	7
25	17.012.0025.11	25X2,3 SDR11 ISO S-5	0.031	25	2,3	52	25	33	58	9
32	17.012.0032.11	32X2,9 SDR11 ISO S-5	0.040	32	2,9	50	25	40	68	10
40	17.012.0040.11	40X3,7 SDR11 ISO S-5	0.061	40	3,7	52	24	50	78	11
50	17.012.0050.11	50X4,6 SDR11 ISO S-5	0.084	50	4,6	53	22	61	88	12
63	17.012.0063.11	63X5,8 SDR11 ISO S-5	0.126	63	5,8	50	20	75	102	14
75	17.012.0075.11	75X6,8 SDR11 ISO S-5	0.194	75	6,8	50,5	18	89	122	16
90	17.012.0090.11	90X8,2 SDR11 ISO S-5	0.322	90	8,2	82	40	105	138	17



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	17.012.0110.11	110X10,0 SDR11 ISO S-5	0.460	110	10	82	38	125	158	18
140	17.012.0140.11	140X12,7 SDR11 ISO S-5	0.698	140	12,7	92	37	155	188	25
160	17.012.0160.11	160X14,6 SDR11 ISO S-5	0.910	160	14,6	92	38	175	212	25