



Flange adaptor DIN injection moulded
Socket-welding PVDF natural

| Size | Code | Detail | Weight | da(OD) mm | L mm | d3 mm | d4 mm | h mm |
|------|----------------|------------------|--------|--------------|------|----------|----------|------|
| 16 | 30.052.0016.07 | 16 - MOP 20 bar | 0.026 | 16 | 20 | 27 | 45 | 6 |
| 20 | 30.052.0020.07 | 20 - MOP 20 bar | 0.022 | 20 | 21 | 27 | 45 | 6 |
| 25 | 30.052.0025.07 | 25 - MOP 20 bar | 0.043 | 25 | 22 | 33 | 58 | 7 |
| 32 | 30.052.0032.07 | 32 - MOP 20 bar | 0.058 | 32 | 25 | 41 | 68 | 7 |
| 40 | 30.052.0040.07 | 40 - MOP 20 bar | 0.075 | 40 | 26 | 50 | 78 | 8 |
| 50 | 30.052.0050.07 | 50 - MOP 20 bar | 0.104 | 50 | 30 | 61 | 88 | 8 |
| 63 | 30.052.0063.07 | 63 - MOP 20 bar | 0.149 | 63 | 33 | 76 | 102 | 9 |
| 75 | 30.052.0075.07 | 75 - MOP 20 bar | 0.239 | 75 | 37 | 90 | 122 | 10 |
| 90 | 30.052.0090.07 | 90 - MOP 20 bar | 0.320 | 90 | 41 | 109 | 125 | 11 |
| 110 | 30.052.0110.07 | 110 - MOP 20 bar | 0.465 | 110 | 48 | 131 | 150 | 12 |