



Reducer concentric injection moulded
Socket-welding PVDF natural

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	L mm
25/16	30.057.2516.07	25/16 - MOP 20 bar	0.020	25	16	40
25/20	30.057.2520.07	25/20 - MOP 20 bar	0.021	25	20	40
32/20	30.057.3220.07	32/20 - MOP 20 bar	0.029	32	20	44
32/25	30.057.3225.07	32/25 - MOP 20 bar	0.035	32	25	44
40/20	30.057.4020.07	40/20 - MOP 20 bar	0.043	40	20	49
40/25	30.057.4025.07	40/25 - MOP 20 bar	0.046	40	25	49,5
40/32	30.057.4032.07	40/32 - MOP 20 bar	0.053	40	32	49
50/20	30.057.5020.07	50/20 - MOP 20 bar	0.064	50	20	55
50/25	30.057.5025.07	50/25 - MOP 20 bar	0.067	50	25	55
50/32	30.057.5032.07	50/32 - MOP 20 bar	0.074	50	32	55
50/40	30.057.5040.07	50/40 - MOP 20 bar	0.085	50	40	55
63/25	30.057.6325.07	63/25 - MOP 20 bar	0.107	63	25	64
63/32	30.057.6332.07	63/32 - MOP 20 bar	0.116	63	32	64,5
63/40	30.057.6340.07	63/40 - MOP 20 bar	0.131	63	40	64
63/50	30.057.6350.07	63/50 - MOP 20 bar	0.148	63	50	64
75/63	30.057.7563.07	75/63 - MOP 20 bar	0.209	75	63	64
90/63	30.057.9063.07	90/63 - MOP 20 bar	0.347	90	63	87
90/75	30.057.9075.07	90/75 - MOP 20 bar	0.359	90	75	87
110/63	30.057.1163.07	110/63 - MOP 20 bar	0.486	110	63	89



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	L mm
110/90	30.057.1190.07	110/90 - MOP 20 bar	0.575	110	90	87