



Tee reduced long spigot injection
moulded Butt + IR + HPF-welding PVDF
natural

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
110/90	30.065.1190.33	110/90 SDR33 ISO S-16	1.005	110	90	3,4	2,8	150	313	87	75
160/90	30.065.1690.33	160/90 SDR33 ISO S-16	2.400	160	90	4,9	2,8	183	348	96	70
160/110	30.065.1611.33	160/110 SDR33 ISO S-16	2.700	160	110	4,9	3,4	183	349	97	81
225/160	30.065.2216.33	225/160 SDR33 ISO S-16	4.320	225	160	6,9	4,9	181	352	68	47
63/20	30.065.6320.21	63/20 SDR21 ISO S-10	0.125	63	20	3	1,9	70,5	97	31	31
63/25	30.065.6325.21	63/25 SDR21 ISO S-10	0.133	63	25	3	1,9	70,5	102	31	31
63/32	30.065.6332.21	63/32 SDR21 ISO S-10	0.147	63	32	3	2,4	70,5	109	31	31
63/40	30.065.6340.21	63/40 SDR21 ISO S-10	0.157	63	40	3	2,4	70,5	117	31	31
63/50	30.065.6350.21	63/50 SDR21 ISO S-10	0.199	63	50	3	3	70,5	127	31	31



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
90/20	30.065.9020.21	90/20 SDR21 ISO S-10	0.663	90	20	4,3	1,9	95	230	53	38
90/25	30.065.9025.21	90/25 SDR21 ISO S-10	0.645	90	25	4,3	1,9	95	230	53	38
90/32	30.065.9032.21	90/32 SDR21 ISO S-10	0.664	90	32	4,3	2,4	95	230	53	38
90/40	30.065.9040.21	90/40 SDR21 ISO S-10	0.674	90	40	4,3	2,4	95	230	53	38
90/50	30.065.9050.21	90/50 SDR21 ISO S-10	0.674	90	50	4,3	3	95	230	53	38
90/63	30.065.9063.21	90/63 SDR21 ISO S-10	0.685	90	63	4,3	3	95	230	53	38
110/20	30.065.1120.21	110/20 SDR21 ISO S-10	0.978	110	20	5,3	1,9	105	230	52	36
110/25	30.065.1125.21	110/25 SDR21 ISO S-10	0.983	110	25	5,3	1,9	105	230	52	36
110/32	30.065.1132.21	110/32 SDR21 ISO S-10	0.997	110	32	5,3	2,4	105	230	52	36
110/40	30.065.1140.21	110/40 SDR21 ISO S-10	0.986	110	40	5,3	2,4	105	230	52	36
110/50	30.065.1150.21	110/50 SDR21 ISO S-10	0.932	110	50	5,3	3	105	230	52	36
110/63	30.065.1163.21	110/63 SDR21 ISO S-10	0.986	110	63	5,3	3	105	230	52	36
110/90	30.065.1190.21	110/90 SDR21 ISO S-10	1.370	110	90	5,3	4,3	150	313	87	75



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
160/63	30.065.1663.21	160/63 SDR21 ISO S-10	2.837	160	63	7,7	3	175	345	100	65
160/90	30.065.1690.21	160/90 SDR21 ISO S-10	3.250	160	90	7,7	4,3	183	348	97	72
160/110	30.065.1611.21	160/110 SDR21 ISO S-10	3.490	160	110	7,7	5,3	183	349	97	81
225/110	30.065.2211.21	225/110 SDR21 ISO S-10	5.697	225	110	10,8	5,3	170	353	67	36
90/63	30.065.9063.31	90/63 SDR33/21 MOP 10 bar	0.582	90	63	2,8	3	130	265	75	65
110/63	30.065.1163.31	110/63 SDR33/21 MOP 10 bar	0.971	110	63	3,4	3	150	315	85	65
160/63	30.065.1663.31	160/63 SDR33/21 MOP 10 bar	2.055	160	63	4,9	3	175	348	100	65
160/90	30.065.1690.31	160/90 SDR33/21 MOP 10 bar	2.520	160	90	4,9	4,3	183	348	97	72
160/110	30.065.1611.31	160/110 SDR33/21 MOP 10 bar	2.830	160	110	4,9	5,3	185	347	96	81
225/90	30.065.2290.31	225/90 SDR33/21 MOP 10 bar	4.401	225	90	6,9	4,3	175	353	67	35
225/110	30.065.2211.31	225/110 SDR33/21 MOP 10 bar	4.266	225	110	6,9	5,3	170	350	67	36