



E-Reducer concentric MOP water
16bar/gas 10bar W/P-TW injection
moulded Electro-fusion PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	L mm	d mm	d1 mm
25/20	70.177.2520.11	25/20 SDR 11	0.056	25	20	108,5	35	37
32/20	70.177.3220.11	32/20 SDR 11	0.068	32	20	108,5	43	43
32/25	70.177.3225.11	32/25 SDR 11	0.068	32	25	108,5	42	44
40/20	70.177.4020.11	40/20 SDR 11	0.092	40	20	118,5	53	48
40/25	70.177.4025.11	40/25 SDR 11	0.095	40	25	118,5	53	48
40/32	70.177.4032.11	40/32 SDR 11	0.100	40	32	118,5	53	47
50/25	70.177.5025.11	50/25 SDR 11	0.143	50	25	133,5	67	49
50/32	70.177.5032.11	50/32 SDR 11	0.149	50	32	133,5	67	53
50/40	70.177.5040.11	50/40 SDR 11	0.165	50	40	133,5	67	53
63/32	70.177.6332.11	63/32 SDR 11	0.223	63	32	132,5	83	56
63/40	70.177.6340.11	63/40 SDR 11	0.240	63	40	132,5	83	56



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	L mm	d mm	d1 mm
63/50	70.177.6350.11	63/50 SDR 11	0.273	63	50	148	83	59,5
75/50	70.177.7550.11	75/50 SDR 11	0.336	75	50	155,5	97	63
75/63	70.177.7563.11	75/63 SDR 17-11	0.366	75	63	155,5	97	63
90/63	70.177.9063.11	90/63 SDR 17-11	0.560	90	63	170	117	73,5
110/63	70.177.1163.11	110/63 SDR 17-11	0.860	110	63	200,5	140,5	84
110/90	70.177.1190.11	110/90 SDR 17-11	0.922	110	90	180,5	140,5	84
125/90	70.177.1290.11	125/90 SDR 17-11	0.992	125	90	183,5	156	90
125/110	70.177.1211.11	125/110 SDR 17-11	1.050	125	110	173	156	90
160/90	70.177.1690.11	160/90 SDR 17-11	1.890	160	90	240	200	108,5
160/110	70.177.1611.11	160/110 SDR 17-11	1.980	160	110	224	200	108,5
225/160	70.177.2216.11	225/160 SDR 17-11	5.120	225	160	282	280	147