



Reducer excentric long spigot W/P-TW  
injection moulded Butt + E-fusion-welding  
PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
63/50	70.069.6350.17	63/50 SDR17 PN10	0.110	63	50	3,8	3	173	72	56
75/50	70.069.7550.17	75/50 SDR17 PN10	0.169	75	50	4,5	3	195	81	56
75/63	70.069.7563.17	75/63 SDR17 PN10	0.160	75	63	4,5	3,8	195	82	63
90/63	70.069.9063.17	90/63 SDR17 PN10	0.250	90	63	5,4	3,8	216	94	64
90/75	70.069.9075.17	90/75 SDR17 PN10	0.284	90	75	5,4	4,5	219	95	70
110/63	70.069.1163.17	110/63 SDR17 PN10	0.410	110	63	6,6	3,8	246	99	63
110/90	70.069.1190.17	110/90 SDR17 PN10	0.460	110	90	6,6	5,4	241	96	79
125/63	70.069.1263.17	125/63 SDR17 PN10	0.570	125	63	7,4	3,8	265	107,5	63



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
125/90	70.069.1290.17	125/90 SDR17 PN10	0.626	125	90	7,4	5,4	264	106,5	79
125/110	70.069.1211.17	125/110 SDR17 PN10	0.679	125	110	7,4	6,6	257	105,5	86
140/125	70.069.1412.17	140/125 SDR17 PN10	0.939	140	125	8,3	7,4	285	111,5	93
160/90	70.069.1690.17	160/90 SDR17 PN10	1.110	160	90	9,5	5,4	310	117,5	79
160/110	70.069.1611.17	160/110 SDR17 PN10	1.183	160	110	9,5	6,6	310	118,5	85
160/125	70.069.1612.17	160/125 SDR17 PN10	1.270	160	125	9,5	7,4	310	118,5	91
160/140	70.069.1614.17	160/140 SDR17 PN10	1.300	160	140	9,5	8,3	309	116,5	96
180/90	70.069.1890.17	180/90 SDR17 PN10	1.640	180	90	10,7	5,4	342	127	79
180/125	70.069.1812.17	180/125 SDR17 PN10	1.770	180	125	10,7	7,4	348	134,5	92,5
180/160	70.069.1816.17	180/160 SDR17 PN10	1.880	180	160	10,7	9,5	340	131,5	101,5
200/160	70.069.2016.17	200/160 SDR17 PN10	3.200	200	160	11,9	9,5	370	138,5	100
200/180	70.069.2018.17	200/180 SDR17 PN10	2.560	200	180	11,9	10,7	370	142,5	107



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
225/160	70.069.2216.17	225/160 SDR17 PN10	4.000	225	160	13,4	9,5	400	151,5	101,5
225/180	70.069.2218.17	225/180 SDR17 PN10	3.310	225	180	13,4	10,7	400	151,5	108,5
225/200	70.069.2220.17	225/200 SDR17 PN10	3.470	225	200	13,4	11,9	400	151,5	115,5
250/200	70.069.2521.17	250/200 SDR17 PN10	5.410	250	200	14,8	11,9	440	180	120
250/225	70.069.2522.17	250/225 SDR17 PN10	4.600	250	225	14,8	13,4	439	182,5	124,5
25/20	70.069.2520.11	25/20 SDR11 PN16	0.021	25	20	3	3	103	51	38
32/25	70.069.3225.11	32/25 SDR11 PN16	0.029	32	25	3	3	114	56	40
40/25	70.069.4025.11	40/25 SDR11 PN16	0.040	40	25	3,7	3	126	60	40
40/32	70.069.4032.11	40/32 SDR11 PN16	0.045	40	32	3,7	3	125	59	44
50/32	70.069.5032.11	50/32 SDR11 PN16	0.080	50	32	4,6	3	156	71	45
50/40	70.069.5040.11	50/40 SDR11 PN16	0.092	50	40	4,6	3,7	157	71	49
63/32	70.069.6332.11	63/32 SDR11 PN16	0.139	63	32	5,8	3	177	75	45



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
63/40	70.069.6340.11	63/40 SDR11 PN16	0.146	63	40	5,8	3,7	177	76	49
63/50	70.069.6350.11	63/50 SDR11 PN16	0.156	63	50	5,8	4,6	177	76	56
75/50	70.069.7550.11	75/50 SDR11 PN16	0.230	75	50	6,8	4,6	195	82	57
75/63	70.069.7563.11	75/63 SDR11 PN16	0.255	75	63	6,8	5,8	197	83	63
90/63	70.069.9063.11	90/63 SDR11 PN16	0.380	90	63	8,2	5,8	213	92	64
90/75	70.069.9075.11	90/75 SDR11 PN16	0.402	90	75	8,2	6,8	214	93	69
110/63	70.069.1163.11	110/63 SDR11 PN16	0.588	110	63	10	5,8	244	99	63
110/90	70.069.1190.11	110/90 SDR11 PN16	0.666	110	90	10	8,2	240	98	79
125/63	70.069.1263.11	125/63 SDR11 PN16	0.820	125	63	11,4	5,8	268	105	63
125/90	70.069.1290.11	125/90 SDR11 PN16	0.910	125	90	11,4	8,2	265	106,5	79
125/110	70.069.1211.11	125/110 SDR11 PN16	0.979	125	110	11,4	10	260	103	87
140/125	70.069.1412.11	140/125 SDR11 PN16	1.320	140	125	12,7	11,4	283	109,5	95



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
160/90	70.069.1690.11	160/90 SDR11 PN16	1.520	160	90	14,6	8,2	309	117,5	79
160/110	70.069.1611.11	160/110 SDR11 PN16	1.630	160	110	14,6	10	305	115,5	87
160/125	70.069.1612.11	160/125 SDR11 PN16	1.690	160	125	14,6	11,4	309	116,5	91
160/140	70.069.1614.11	160/140 SDR11 PN16	1.880	160	140	14,6	12,7	308	116,5	97,5
180/90	70.069.1890.11	180/90 SDR11 PN16	2.260	180	90	16,4	8,2	348	128,5	79
180/125	70.069.1812.11	180/125 SDR11 PN16	2.456	180	125	16,4	11,4	345	130	93
180/160	70.069.1816.11	180/160 SDR11 PN16	2.780	180	160	16,4	14,6	345	130	104
200/160	70.069.2016.11	200/160 SDR11 PN16	3.320	200	160	18,2	14,6	373	138,5	104
200/180	70.069.2018.11	200/180 SDR11 PN16	3.670	200	180	18,2	16,4	373	143,5	111
225/160	70.069.2216.11	225/160 SDR11 PN16	4.370	225	160	20,5	14,6	402	154,5	100
225/180	70.069.2218.11	225/180 SDR11 PN16	4.620	225	180	20,5	16,4	403	154,5	110
225/200	70.069.2220.11	225/200 SDR11 PN16	4.950	225	200	20,5	18,2	403	155,5	115



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
250/200	70.069.2521.11	250/200 SDR11 PN16	6.280	250	200	22,7	18,2	440	180	120
250/225	70.069.2522.11	250/225 SDR11 PN16	6.840	250	225	22,7	20,5	440	179	125