



Reducer concentric short spigot injection moulded Butt-welding PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
160/110	70.009.1611.26	160/110 SDR26 ISO S-12,5	0.200	160	110	6,2	4,2	101,5	40	28
200/160	70.009.2016.26	200/160 SDR26 ISO S-12,5	0.800	200	160	7,7	6,2	131,5	50	40
225/160	70.009.2216.26	225/160 SDR26 ISO S-12,5	1.110	225	160	8,6	6,2	150	55	40
250/160	70.009.2516.26	250/160 SDR26 ISO S-12,5	1.000	250	160	9,6	6,2	160	60	40
250/200	70.009.2521.26	250/200 SDR26 ISO S-12,5	1.200	250	200	9,6	7,7	158	60	50
250/225	70.009.2522.26	250/225 SDR26 ISO S-12,5	1.300	250	225	9,6	8,6	158	60	55



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
315/200	70.009.3120.26	315/200 SDR26 ISO S-12,5	2.800	315	200	12,1	7,7	199	80	49
315/225	70.009.3122.26	315/225 SDR26 ISO S-12,5	2.900	315	225	12,1	8,6	200	80	57
315/250	70.009.3125.26	315/250 SDR26 ISO S-12,5	3.000	315	250	12,1	9,6	197,5	80	60
75/63	70.009.7563.17	75/63 SDR17 ISO S-8	0.055	75	63	4,5	3,8	60	19	18
90/63	70.009.9063.17	90/63 SDR17 ISO S-8	0.088	90	63	5,4	3,8	68	22	18
90/75	70.009.9075.17	90/75 SDR17 ISO S-8	0.100	90	75	5,4	4,5	68	22	19
110/63	70.009.1163.17	110/63 SDR17 ISO S-8	0.170	110	63	6,6	3,8	88	28	18
110/75	70.009.1175.17	110/75 SDR17 ISO S-8	0.170	110	75	6,6	4,5	85	28	19
110/90	70.009.1190.17	110/90 SDR17 ISO S-8	0.180	110	90	6,6	5,4	85	28	22
125/63	70.009.1263.17	125/63 SDR17 ISO S-8	0.200	125	63	7,4	3,8	91	32	18
125/75	70.009.1275.17	125/75 SDR17 ISO S-8	0.227	125	75	7,4	4,5	100	32	19



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
125/90	70.009.1290.17	125/90 SDR17 ISO S-8	0.210	125	90	7,4	5,4	86	32	22
125/110	70.009.1211.17	125/110 SDR17 ISO S-8	0.230	125	110	7,4	6,6	89	32	28
140/75	70.009.1475.17	140/75 SDR17 ISO S-8	0.340	140	75	8,3	4,5	110	35	19
140/90	70.009.1490.17	140/90 SDR17 ISO S-8	0.320	140	90	8,3	5,4	110	35	22
140/110	70.009.1411.17	140/110 SDR17 ISO S-8	0.335	140	110	8,3	6,6	100	35	28
140/125	70.009.1412.17	140/125 SDR17 ISO S-8	0.290	140	125	8,3	7,4	95	35	32
160/90	70.009.1690.17	160/90 SDR17 ISO S-8	0.350	160	90	9,5	5,4	101,5	40	22
160/110	70.009.1611.17	160/110 SDR17 ISO S-8	0.390	160	110	9,5	6,6	101,5	40	28
160/125	70.009.1612.17	160/125 SDR17 ISO S-8	0.440	160	125	9,5	7,4	114	40	32
160/140	70.009.1614.17	160/140 SDR17 ISO S-8	0.494	160	140	9,5	8,3	118	40	35
180/90	70.009.1890.17	180/90 SDR17 ISO S-8	0.660	180	90	10,7	5,4	136	45	22
180/110	70.009.1811.17	180/110 SDR17 ISO S-8	0.702	180	110	10,7	6,6	136	45	28



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
180/125	70.009.1812.17	180/125 SDR17 ISO S-8	0.661	180	125	10,7	7,4	134	45	32
180/140	70.009.1814.17	180/140 SDR17 ISO S-8	0.750	180	140	10,7	8,3	136	45	35
180/160	70.009.1816.17	180/160 SDR17 ISO S-8	0.750	180	160	10,7	9,5	130	45	40
200/140	70.009.2014.17	200/140 SDR17 ISO S-8	0.793	200	140	11,9	8,3	137	50	35
200/160	70.009.2016.17	200/160 SDR17 ISO S-8	0.854	200	160	11,9	9,5	131,5	50	40
200/180	70.009.2018.17	200/180 SDR17 ISO S-8	0.920	200	180	11,9	10,7	137	50	45
225/140	70.009.2214.17	225/140 SDR17 ISO S-8	1.210	225	140	13,4	8,3	155	55	35
225/160	70.009.2216.17	225/160 SDR17 ISO S-8	1.150	225	160	13,4	9,5	150	55	40
225/180	70.009.2218.17	225/180 SDR17 ISO S-8	1.226	225	180	13,4	10,7	151	55	45
225/200	70.009.2220.17	225/200 SDR17 ISO S-8	1.290	225	200	13,4	11,9	149	55	50
250/160	70.009.2516.17	250/160 SDR17 ISO S-8	1.390	250	160	14,8	9,5	160	60	40
250/180	70.009.2518.17	250/180 SDR17 ISO S-8	1.545	250	180	14,8	10,7	155	59	45



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
250/200	70.009.2521.17	250/200 SDR17 ISO S-8	1.590	250	200	14,8	11,9	158	60	50
250/225	70.009.2522.17	250/225 SDR17 ISO S-8	1.670	250	225	14,8	13,4	158	60	55
280/200	70.009.2820.17	280/200 SDR17 ISO S-8	2.348	280	200	16,6	11,9	191	70	50
280/225	70.009.2822.17	280/225 SDR17 ISO S-8	2.335	280	225	16,6	13,4	190	70	55
280/250	70.009.2825.17	280/250 SDR17 ISO S-8	2.690	280	250	16,6	14,8	193	70	60
315/200	70.009.3120.17	315/200 SDR17 ISO S-8	3.180	315	200	18,7	11,9	199	80	49
315/225	70.009.3122.17	315/225 SDR17 ISO S-8	3.300	315	225	18,7	13,4	200	80	57
315/250	70.009.3125.17	315/250 SDR17 ISO S-8	3.175	315	250	18,7	14,8	197,5	80	60
315/280	70.009.3128.17	315/280 SDR17 ISO S-8	3.396	315	280	18,7	16,6	198	80	70
25/20	70.009.2520.11	25/20 SDR11 ISO S-5	0.007	25	20	3	3	33	14	14
32/20	70.009.3220.11	32/20 SDR11 ISO S-5	0.009	32	20	3	3	40	14	14
32/25	70.009.3225.11	32/25 SDR11 ISO S-5	0.010	32	25	3	3	40	14	14



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
40/20	70.009.4020.11	40/20 SDR11 ISO S-5	0.014	40	20	3,7	3	42	14	14
40/25	70.009.4025.11	40/25 SDR11 ISO S-5	0.015	40	25	3,7	3	42	14	14
40/32	70.009.4032.11	40/32 SDR11 ISO S-5	0.016	40	32	3,7	3	39	14	14
50/25	70.009.5025.11	50/25 SDR11 ISO S-5	0.023	50	25	4,6	3	47	14	14
50/32	70.009.5032.11	50/32 SDR11 ISO S-5	0.022	50	32	4,6	3	41	14	14
50/40	70.009.5040.11	50/40 SDR11 ISO S-5	0.028	50	40	4,6	3,7	47	14	14
63/32	70.009.6332.11	63/32 SDR11 ISO S-5	0.040	63	32	5,8	3	57	18	14
63/40	70.009.6340.11	63/40 SDR11 ISO S-5	0.045	63	40	5,8	3,7	52	18	14
63/50	70.009.6350.11	63/50 SDR11 ISO S-5	0.053	63	50	5,8	4,6	57	18	14
75/32	70.009.7532.11	75/32 SDR11 ISO S-5	0.071	75	32	6,8	3	75	19	14
75/40	70.009.7540.11	75/40 SDR11 ISO S-5	0.080	75	40	6,8	3,7	70	19	14
75/50	70.009.7550.11	75/50 SDR11 ISO S-5	0.077	75	50	6,8	4,6	63	19	14



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
75/63	70.009.7563.11	75/63 SDR11 ISO S-5	0.077	75	63	6,8	5,8	59	19	18
90/50	70.009.9050.11	90/50 SDR11 ISO S-5	0.116	90	50	8,2	4,6	76	22	14
90/63	70.009.9063.11	90/63 SDR11 ISO S-5	0.113	90	63	8,2	5,8	68	22	18
90/75	70.009.9075.11	90/75 SDR11 ISO S-5	0.128	90	75	8,2	6,8	68	22	19
110/50	70.009.1150.11	110/50 SDR11 ISO S-5	0.200	110	50	10	4,6	90	28	14
110/63	70.009.1163.11	110/63 SDR11 ISO S-5	0.200	110	63	10	5,8	88	28	18
110/75	70.009.1175.11	110/75 SDR11 ISO S-5	0.215	110	75	10	6,8	85	28	19
110/90	70.009.1190.11	110/90 SDR11 ISO S-5	0.230	110	90	10	8,2	85	28	22
125/63	70.009.1263.11	125/63 SDR11 ISO S-5	0.293	125	63	11,4	5,8	100	32	18
125/75	70.009.1275.11	125/75 SDR11 ISO S-5	0.320	125	75	11,4	6,8	100	32	19
125/90	70.009.1290.11	125/90 SDR11 ISO S-5	0.304	125	90	11,4	8,2	89	32	22
125/110	70.009.1211.11	125/110 SDR11 ISO S-5	0.329	125	110	11,4	10	89	32	28



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
140/75	70.009.1475.11	140/75 SDR11 ISO S-5	0.400	140	75	12,7	6,8	110	35	19
140/90	70.009.1490.11	140/90 SDR11 ISO S-5	0.440	140	90	12,7	8,2	110	35	22
140/110	70.009.1411.11	140/110 SDR11 ISO S-5	0.425	140	110	12,7	10	100	35	28
140/125	70.009.1412.11	140/125 SDR11 ISO S-5	0.445	140	125	12,7	11,4	92	35	32
160/90	70.009.1690.11	160/90 SDR11 ISO S-5	0.520	160	90	14,6	8,2	100	40	22
160/110	70.009.1611.11	160/110 SDR11 ISO S-5	0.565	160	110	14,6	10	105	40	28
160/125	70.009.1612.11	160/125 SDR11 ISO S-5	0.650	160	125	14,6	11,4	114	40	32
160/140	70.009.1614.11	160/140 SDR11 ISO S-5	0.660	160	140	14,6	12,7	114	40	35
180/90	70.009.1890.11	180/90 SDR11 ISO S-5	0.810	180	90	16,4	8,2	140	45	28
180/110	70.009.1811.11	180/110 SDR11 ISO S-5	0.860	180	110	16,4	10	136	45	28
180/125	70.009.1812.11	180/125 SDR11 ISO S-5	0.865	180	125	16,4	11,4	134	45	32
180/140	70.009.1814.11	180/140 SDR11 ISO S-5	1.030	180	140	16,4	12,7	136	45	35



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
180/160	70.009.1816.11	180/160 SDR11 ISO S-5	0.960	180	160	16,4	14,6	130	45	40
200/140	70.009.2014.11	200/140 SDR11 ISO S-5	1.110	200	140	18,2	12,7	137	50	35
200/160	70.009.2016.11	200/160 SDR11 ISO S-5	1.240	200	160	18,2	14,6	134	50	40
200/180	70.009.2018.11	200/180 SDR11 ISO S-5	1.361	200	180	18,2	16,4	137	50	45
225/140	70.009.2214.11	225/140 SDR11 ISO S-5	1.545	225	140	20,5	12,7	155	55	35
225/160	70.009.2216.11	225/160 SDR11 ISO S-5	1.560	225	160	20,5	14,6	150	55	40
225/180	70.009.2218.11	225/180 SDR11 ISO S-5	1.625	225	180	20,5	16,4	151	55	45
225/200	70.009.2220.11	225/200 SDR11 ISO S-5	1.794	225	200	20,5	18,2	149	55	50
250/160	70.009.2516.11	250/160 SDR11 ISO S-5	2.030	250	160	22,7	14,6	160	60	45
250/180	70.009.2518.11	250/180 SDR11 ISO S-5	2.120	250	180	22,7	16,4	157	60	45
250/200	70.009.2521.11	250/200 SDR11 ISO S-5	2.210	250	200	22,7	18,2	158,5	60	50
250/225	70.009.2522.11	250/225 SDR11 ISO S-5	2.410	250	225	22,7	20,5	159	60	55



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
280/200	70.009.2820.11	280/200 SDR11 ISO S-5	3.140	280	200	25,4	18,2	188	70	50
280/225	70.009.2822.11	280/225 SDR11 ISO S-5	3.340	280	225	25,4	20,5	188	70	55
280/250	70.009.2825.11	280/250 SDR11 ISO S-5	3.120	280	250	25,4	22,7	165	70	60
315/200	70.009.3120.11	315/200 SDR11 ISO S-5	4.140	315	200	28,6	18,2	200	80	50
315/225	70.009.3122.11	315/225 SDR11 ISO S-5	4.390	315	225	28,6	20,5	200	80	55
315/250	70.009.3125.11	315/250 SDR11 ISO S-5	4.340	315	250	28,6	22,7	197,5	80	60
315/280	70.009.3128.11	315/280 SDR11 ISO S-5	4.560	315	280	28,6	25,4	197,5	80	70