



Pressure Tapping Valve brass-
valve+integrated cutter W/P-TW injection
moulded Electro-fusion PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	z mm	L1 mm	h mm
63/32	70.079.6332.11	63/32 SDR11 PN16	1.603	63	32	65,3	131	163
63/40	70.079.6340.11	63/40 SDR11 PN16	1.580	63	40	65,3	140	163
63/50	70.079.6350.11	63/50 SDR11 PN16	1.647	63	50	65,3	160,5	163
63/63	70.079.6363.11	63/63 SDR11 PN16	1.710	63	63	65,3	187	163
90/32	70.079.9032.11	90/32 SDR 17 - 11 PN16	2.380	90	32	79	135	203
90/40	70.079.9040.11	90/40 SDR 17 - 11 PN16	2.410	90	40	79	145	203
90/50	70.079.9050.11	90/50 SDR 17 - 11 PN16	2.440	90	50	79	161	203
90/63	70.079.9063.11	90/63 SDR 17 - 11 PN16	2.480	90	63	79	192	203
110/32	70.079.1132.11	110/32 SDR 17 - 11 PN16	2.190	110	32	87	137	202
110/40	70.079.1140.11	110/40 SDR 17 - 11 PN16	2.498	110	40	87	147	203
110/50	70.079.1150.11	110/50 SDR 17 - 11 PN16	2.476	110	50	87	160	203



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	z mm	L1 mm	h mm
110/63	70.079.1163.11	110/63 SDR 17 - 11 PN16	2.560	110	63	87	192,6	203
125/32	70.079.1232.11	125/32 SDR 17 - 11 PN16	2.490	125	32	95,9	137	203
125/40	70.079.1240.11	125/40 SDR 17 - 11 PN16	2.491	125	40	95,9	147	203
125/50	70.079.1250.11	125/50 SDR 17 - 11 PN16	2.520	125	50	95,9	161	203
125/63	70.079.1263.11	125/63 SDR 17 - 11 PN16	2.610	125	63	95,9	192	203
140/32	70.079.1432.11	140/32 SDR 17 - 11 PN16	2.460	140	32	103,5	137	203
140/40	70.079.1440.11	140/40 SDR 17 - 11 PN16	2.500	140	40	103,5	147	203
140/50	70.079.1450.11	140/50 SDR 17 - 11 PN16	2.520	140	50	103,5	161	203
140/63	70.079.1463.11	140/63 SDR 17 - 11 PN16	2.600	140	63	103,4	192	203
160/32	70.079.1632.11	160/32 SDR 17 - 11 PN16	2.550	160	32	103,4	137	203
160/40	70.079.1640.11	160/40 SDR 17 - 11 PN16	2.560	160	40	113,2	147	203
160/50	70.079.1650.11	160/50 SDR 17 - 11 PN16	2.600	160	50	113,2	161	203
160/63	70.079.1663.11	160/63 SDR 17 - 11 PN16	2.680	160	63	113,2	189	203
180/32	70.079.1832.11	180/32 SDR 17 - 11 PN16	2.644	180	32	123	137	203
180/40	70.079.1840.11	180/40 SDR 17 - 11 PN16	2.623	180	40	123	147	203
180/50	70.079.1850.11	180/50 SDR 17 - 11 PN16	2.689	180	50	123	161	203
180/63	70.079.1863.11	180/63 SDR 17 - 11 PN16	2.772	180	63	123	189	203



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	z mm	L1 mm	h mm
200/32	70.079.2032.11	200/32 SDR 17 - 11 PN16	2.502	200	32	134	137	203
200/40	70.079.2040.11	200/40 SDR 17 - 11 PN16	2.500	200	40	134	146	203
200/50	70.079.2050.11	200/50 SDR 17 - 11 PN16	2.550	200	50	134	159	203
200/63	70.079.2063.11	200/63 SDR 17 - 11 PN16	2.620	200	63	134	191	203
225/32	70.079.2232.11	225/32 SDR 17 - 11 PN16	2.550	225	32	147,6	137	203
225/40	70.079.2240.11	225/40 SDR 17 - 11 PN16	2.340	225	40	147,6	147	203
225/50	70.079.2250.11	225/50 SDR 17 - 11 PN16	2.600	225	50	147,6	160	203
225/63	70.079.2263.11	225/63 SDR 17 - 11 PN16	2.600	225	63	147,6	192	203
250/63	70.079.2563.11	250/63 SDR 17 - 11 PN16	2.495	250	63	169,6	224,5	203
280/63	70.079.2863.11	280/63 SDR 17 - 11 PN16	2.765	280	63	184,6	224,5	203
315/63	70.079.3163.11	315/63 SDR 17 - 11 PN16	2.510	315	63	203,6	192	203
355/63	70.079.3563.11	355/63 SDR 17 - 11 PN16	2.800	355	63	203	192	203