



Bend 45° segmented derating factor 0.8  
Butt-welding PE 100-RC black

| Size | Code           | Detail                   | Weight  | da(OD)<br>mm | s mm | r mm  | z mm  |
|------|----------------|--------------------------|---------|--------------|------|-------|-------|
| 560  | 70.330.0560.41 | 560X13,7 SDR41 ISO S-20  | 27.890  | 560          | 13,7 | 840   | 587   |
| 630  | 70.330.0630.41 | 630X15,4 SDR41 ISO S-20  | 36.000  | 630          | 15,4 | 945   | 616   |
| 710  | 70.330.0710.41 | 710X17,4 SDR41 ISO S-20  | 52.000  | 710          | 17,4 | 1.065 | 700   |
| 800  | 70.330.0800.41 | 800X19,6 SDR41 ISO S-20  | 70.000  | 800          | 19,6 | 1.200 | 738   |
| 900  | 70.330.0900.41 | 900X22,0 SDR41 ISO S-20  | 93.000  | 900          | 22   | 1.330 | 780   |
| 1000 | 70.330.1000.41 | 1000X24,5 SDR41 ISO S-20 | 136.000 | 1.000        | 24,5 | 1.500 | 923   |
| 1200 | 70.330.1200.41 | 1200X29,4 SDR41 ISO S-20 | 214.000 | 1.200        | 29,4 | 1.800 | 1.007 |
| 1400 | 70.330.1400.41 | 1400X34,3 SDR41 ISO S-20 | 290.000 | 1.400        | 34,3 | 1.705 | 1.006 |
| 1600 | 70.330.1600.41 | 1600X39,2 SDR41 ISO S-20 | 404.000 | 1.600        | 39,2 | 1.920 | 1.073 |
| 1800 | 70.330.1800.41 | 1800X44,0 SDR41 ISO S-20 | 543.000 | 1.800        | 44   | 2.160 | 1.144 |
| 2000 | 70.330.2000.41 | 2000X48,9 SDR41 ISO S-20 | 711.000 | 2.000        | 48,9 | 2.400 | 1.216 |
| 2250 | 70.330.2250.41 | 2250X55,0 SDR41 ISO S-20 | 965.000 | 2.250        | 55   | 2.700 | 1.305 |
| 560  | 70.330.0560.33 | 560X17,2 SDR33 ISO S-16  | 34.660  | 560          | 17,2 | 840   | 587   |
| 630  | 70.330.0630.33 | 630X19,3 SDR33 ISO S-16  | 45.000  | 630          | 19,3 | 945   | 616   |
| 710  | 70.330.0710.33 | 710X21,8 SDR33 ISO S-16  | 65.000  | 710          | 21,8 | 1.065 | 700   |



| Size | Code           | Detail                     | Weight    | da(OD)<br>mm | s mm | r mm  | z mm  |
|------|----------------|----------------------------|-----------|--------------|------|-------|-------|
| 800  | 70.330.0800.33 | 800X24,5 SDR33 ISO S-16    | 87.000    | 800          | 24,5 | 1.200 | 738   |
| 900  | 70.330.0900.33 | 900X27,6 SDR33 ISO S-16    | 116.000   | 900          | 27,6 | 1.330 | 780   |
| 1000 | 70.330.1000.33 | 1000X30,6 SDR33 ISO S-16   | 169.000   | 1.000        | 30,6 | 1.500 | 923   |
| 1200 | 70.330.1200.33 | 1200X36,7 SDR33 ISO S-16   | 265.000   | 1.200        | 36,7 | 1.800 | 1.007 |
| 1600 | 70.330.1600.33 | 1600X49,0 SDR33 ISO S-16   | 501.000   | 1.600        | 49   | 1.920 | 1.073 |
| 1800 | 70.330.1800.33 | 1800X55,1 SDR33 ISO S-16   | 676.000   | 1.800        | 55,1 | 2.160 | 1.144 |
| 2000 | 70.330.2000.33 | 2000X61,2 SDR33 ISO S-16   | 885.000   | 2.000        | 61,2 | 2.400 | 1.216 |
| 2250 | 70.330.2250.33 | 2250X68,9 SDR33 ISO S-16   | 1,200.000 | 2.250        | 68,9 | 2.700 | 1.305 |
| 560  | 70.330.0560.26 | 560X21,4 SDR26 ISO S-12,5  | 42.300    | 560          | 21,4 | 840   | 587   |
| 630  | 70.330.0630.26 | 630X24,1 SDR26 ISO S-12,5  | 56.000    | 630          | 24,1 | 945   | 616   |
| 710  | 70.330.0710.26 | 710X27,2 SDR26 ISO S-12,5  | 80.000    | 710          | 27,2 | 1.065 | 700   |
| 800  | 70.330.0800.26 | 800X30,6 SDR26 ISO S-12,5  | 107.000   | 800          | 30,6 | 1.200 | 738   |
| 900  | 70.330.0900.26 | 900X34,4 SDR26 ISO S-12,5  | 143.000   | 900          | 34,4 | 1.330 | 780   |
| 1000 | 70.330.1000.26 | 1000X38,2 SDR26 ISO S-12,5 | 210.000   | 1.000        | 38,2 | 1.500 | 923   |
| 1200 | 70.330.1200.26 | 1200X45,8 SDR26 ISO S-12,5 | 328.000   | 1.200        | 45,9 | 1.800 | 1.007 |
| 1400 | 70.330.1400.26 | 1400X53,5 SDR26 ISO S-12,5 | 447.000   | 1.400        | 53,5 | 1.705 | 1.006 |
| 1600 | 70.330.1600.26 | 1600X61,2 SDR26 ISO S-12,5 | 621.000   | 1.600        | 61,2 | 1.920 | 1.073 |
| 1800 | 70.330.1800.26 | 1800X68,8 SDR26 ISO S-12,5 | 836.000   | 1.800        | 68,8 | 2.160 | 1.144 |



| Size | Code           | Detail                     | Weight    | da(OD)<br>mm | s mm  | r mm  | z mm  |
|------|----------------|----------------------------|-----------|--------------|-------|-------|-------|
| 2000 | 70.330.2000.26 | 2000X76,4 SDR26 ISO S-12,5 | 1,095.000 | 2.000        | 76,4  | 2.400 | 1.216 |
| 2250 | 70.330.2250.26 | 2250X86,0 SDR26 ISO S-12,5 | 1,485.000 | 2.250        | 86    | 2.700 | 1.305 |
| 560  | 70.330.0560.17 | 560X33,2 SDR17 ISO S-8     | 64.000    | 560          | 33,2  | 840   | 587   |
| 630  | 70.330.0630.17 | 630X37,4 SDR17 ISO S-8     | 84.000    | 630          | 37,4  | 945   | 616   |
| 710  | 70.330.0710.17 | 710X42,1 SDR17 ISO S-8     | 122.000   | 710          | 42,1  | 1.065 | 700   |
| 800  | 70.330.0800.17 | 800X47,4 SDR17 ISO S-8     | 162.000   | 800          | 47,4  | 1.200 | 738   |
| 900  | 70.330.0900.17 | 900X53,3 SDR17 ISO S-8     | 216.000   | 900          | 53,3  | 1.350 | 780   |
| 1000 | 70.330.1000.17 | 1000X59,2 SDR17 ISO S-8    | 317.000   | 1.000        | 59,3  | 1.500 | 923   |
| 1200 | 70.330.1200.17 | 1200X71,1 SDR17 ISO S-8    | 496.000   | 1.200        | 71,1  | 1.800 | 1.007 |
| 1400 | 70.330.1400.17 | 1400X83,0 SDR17 ISO S-8    | 676.000   | 1.400        | 83    | 1.705 | 1.006 |
| 1600 | 70.330.1600.17 | 1600X94,8 SDR17 ISO S-8    | 939.000   | 1.600        | 94,8  | 1.920 | 1.073 |
| 1800 | 70.330.1800.17 | 1800X106,6 SDR17 ISO S-8   | 1,265.000 | 1.800        | 106,6 | 2.160 | 1.144 |
| 2000 | 70.330.2000.17 | 2000X118,5 SDR17 ISO S-8   | 1,658.000 | 2.000        | 118,5 | 2.400 | 1.216 |
| 2250 | 70.330.2250.17 | 2250X133,3 SDR17 ISO S-8   | 2,248.000 | 2.250        | 133,3 | 2.700 | 1.305 |
| 560  | 70.330.0560.11 | 560X50,8 SDR11 ISO S-5     | 94.300    | 560          | 50,8  | 840   | 587   |
| 630  | 70.330.0630.11 | 630X57,2 SDR11 ISO S-5     | 124.000   | 630          | 57,2  | 945   | 616   |
| 710  | 70.330.0710.11 | 710X64,5 SDR11 ISO S-5     | 179.000   | 710          | 64,5  | 1.065 | 700   |
| 800  | 70.330.0800.11 | 800x72,6 SDR11 ISO S-5     | 239.000   | 800          | 72,6  | 1.200 | 738   |
| 900  | 70.330.0900.11 | 900X81,7 SDR11 ISO S-5     | 320.000   | 900          | 81,7  | 1.350 | 780   |
| 1000 | 70.330.1000.11 | 1000X90,8 SDR11 ISO S-5    | 468.000   | 1.000        | 90,8  | 1.500 | 923   |
| 1200 | 70.330.1200.11 | 1200X108,9 SDR11 ISO S-5   | 733.000   | 1.200        | 108,9 | 1.800 | 1.007 |
| 1400 | 70.330.1400.11 | 1400X127,0 SDR11 ISO S-5   | 998.000   | 1.400        | 127   | 1.705 | 1.006 |
| 1600 | 70.330.1600.11 | 1600X145,2 SDR11 ISO S-5   | 1,387.000 | 1.600        | 145,2 | 1.920 | 1.073 |