



Bend 90° 5 segments derating factor 0.8  
Butt-welding PE 100-RC black

| Size | Code           | Detail                     | Weight    | da(OD)<br>mm | s mm  | r mm  | z mm  |
|------|----------------|----------------------------|-----------|--------------|-------|-------|-------|
| 1400 | 70.332.1400.41 | 1400X34,3 SDR41 ISO S-20   | 493.000   | 1.400        | 34,3  | 1.705 | 2.005 |
| 1600 | 70.332.1600.41 | 1600X39,2 SDR41 ISO S-20   | 701.000   | 1.600        | 39,2  | 1.920 | 2.197 |
| 1600 | 70.332.1600.33 | 1600X49,0 SDR33 ISO S-16   | 869.000   | 1.600        | 49    | 1.920 | 2.197 |
| 1400 | 70.332.1400.26 | 1400X53,5 SDR26 ISO S-12,5 | 756.000   | 1.400        | 53,5  | 1.705 | 2.005 |
| 1600 | 70.332.1600.26 | 1600X61,2 SDR26 ISO S-12,5 | 1,077.000 | 1.600        | 61,2  | 1.920 | 2.197 |
| 1400 | 70.332.1400.17 | 1400X83,0 SDR17 ISO S-8    | 1,145.000 | 1.400        | 83    | 1.705 | 2.005 |
| 1600 | 70.332.1600.17 | 1600X94,8 SDR17 ISO S-8    | 1,628.000 | 1.600        | 94,8  | 1.920 | 2.197 |
| 1400 | 70.332.1400.11 | 1400X127 SDR11 ISO S-5     | 1,145.000 | 1.400        | 127   | 1.705 | 2.005 |
| 1600 | 70.332.1600.11 | 1600X145,2 SDR11 ISO S-5   | 1,628.000 | 1.600        | 145,2 | 1.920 | 2.197 |