



Reducer concentric long spigot W/P-TW  
injection moulded Butt + E-fusion-welding  
PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
90/63	70.067.9063.11	90/63 SDR11 PN16	0.286	90	63	8,2	5,8	172	79	63
110/63	70.067.1163.11	110/63 SDR11 PN16	0.420	110	63	10	5,8	178	82	63
110/90	70.067.1190.11	110/90 SDR11 PN16	0.499	110	90	10	8,2	177	82	79
125/63	70.067.1263.11	125/63 SDR11 PN16	0.560	125	63	11,4	5,8	195	87	63
125/90	70.067.1290.11	125/90 SDR11 PN16	0.635	125	90	11,4	8,2	200	87,5	79
125/110	70.067.1211.11	125/110 SDR11 PN16	0.710	125	110	11,4	10	200	87,5	82
140/125	70.067.1412.11	140/125 SDR11 PN16	0.971	140	125	12,7	11,4	211	94,5	88,5
160/90	70.067.1690.11	160/90 SDR11 PN16	1.010	160	90	14,6	8,2	217	100,5	79



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
160/110	70.067.1611.11	160/110 SDR11 PN16	1.140	160	110	14,6	10	222	98	88
160/125	70.067.1612.11	160/125 SDR11 PN16	1.270	160	125	14,6	11,4	231	98	89,5
160/140	70.067.1614.11	160/140 SDR11 PN16	1.360	160	140	14,6	12,7	229	98	92
180/125	70.067.1812.11	180/125 SDR11 PN16	1.610	180	125	16,4	11,4	245	110	94,5
180/160	70.067.1816.11	180/160 SDR11 PN16	1.860	180	160	16,4	14,6	245	105	104
200/160	70.067.2016.11	200/160 SDR11 PN16	2.250	200	160	18,2	14,6	252	112	98,5
225/160	70.067.2216.11	225/160 SDR11 PN16	2.760	225	160	20,5	14,6	262	120	101
250/160	70.067.2516.11	250/160 SDR11 PN16	3.980	250	160	22,7	14,6	314	153,5	111,5
250/225	70.067.2522.11	250/225 SDR11 PN16	4.740	250	225	22,7	20,5	315	153	131,5
280/250	70.067.2825.11	280/250 SDR11 PN16	6.640	280	250	25,4	22,7	355	163,5	158
315/225	70.067.3122.11	315/225 SDR11 PN16	7.840	315	225	28,6	20,5	375	170,5	131,5
315/250	70.067.3125.11	315/250 SDR11 PN16	8.320	315	250	28,6	22,7	375	174	158