



Tee short spigot injection moulded Butt-welding PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
63	70.006.0063.11	63X5,8 SDR11 ISO S-5	0.228	63	5,8	72	142	25
75	70.006.0075.11	75X6,8 SDR11 ISO S-5	0.408	75	6,8	75	152	15
90	70.006.0090.11	90X8,2 SDR11 ISO S-5	0.701	90	8,2	105	212	38
110	70.006.0110.11	110X10,0 SDR11 ISO S-5	1.240	110	10	122	253	51
125	70.006.0125.11	125X11,4 SDR11 ISO S-5	1.660	125	11,4	140	277	52
140	70.006.0140.11	140X12,7 SDR11 ISO S-5	2.480	140	12,7	150,5	301	57
160	70.006.0160.11	160X14,6 SDR11 ISO S-5	3.440	160	14,6	170	340	57
180	70.006.0180.11	180X16,4 SDR11 ISO S-5	4.600	180	16,4	182,5	365	57
200	70.006.0200.11	200X18,2 SDR11 ISO S-5	6.320	200	18,2	200	400	57
225	70.006.0225.11	225X20,5 SDR11 ISO S-5	8.560	225	20,5	220	440	57
250	70.006.0250.11	250X22,7 SDR11 ISO S-5	11.160	250	22,7	235	466	72



Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
280	70.006.0280.11	280X25,4 SDR11 ISO S-5	16.200	280	25,4	270	536	80
315	70.006.0315.11	315X28,6 SDR11 ISO S-5	19.700	315	28,6	270	540	80
355	70.006.0355.11	355X32,2 SDR11 ISO S-5	31.340	355	32,2	340	680	105
400	70.006.0400.11	400X36,3 SDR11 ISO S-5	39.300	400	36,3	350	695	103
450	70.006.0450.11	450X40,9 SDR11 ISO S-5	65.520	450	40,9	450	890	130
500	70.006.0500.11	500X45,4 SDR11 ISO S-5	73.720	500	45,4	450	900	130