



Chamfered Stub Flange DIN for butterfly valves injection moulded+chamfered  
Butt-welding PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d mm	d3 mm	d4 mm	h mm
90	70.012.9090.11	90X8,2 SDR11 ISO S-5	0.332	90	8,2	80	40	80	105	138	17
110	70.012.9110.11	110X10,0 SDR11 ISO S-5	0.458	110	10	80	38	100	125	158	18
140	70.012.9140.11	140X12,7 SDR11 ISO S-5	0.775	140	12,7	92	37	125	155	188	25
160	70.012.9160.11	160X14,6 SDR11 ISO S-5	0.987	160	14,6	92	38	150	175	212	25
180	70.012.9180.11	180X16,4 SDR11 ISO S-5	1.040	180	16,4	93	43	150	183	212	30
200	70.012.9200.11	200X18,2 SDR11 ISO S-5	1.840	200	18,2	114	40	210	232	268	32
225	70.012.9225.11	225X20,5 SDR11 ISO S-5	1.950	225	20,5	113	52	210	235	268	32
250	70.012.9250.11	250X22,7 SDR11 ISO S-5	3.020	250	22,7	130	58	255	285	320	35



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d mm	d3 mm	d4 mm	h mm
280	70.012.9280.11	280X25,4 SDR11 ISO S-5	3.240	280	25,4	128	58	255	288	320	35
315	70.012.9315.11	315X28,6 SDR11 ISO S-5	4.230	315	28,6	136	65	301	335	370	35
355	70.012.9355.11	355X32,2 SDR11 ISO S-5	6.200	355	32,2	150	70	338	373	430	40
400	70.012.9400.11	400X36,3 SDR11 ISO S-5	8.400	400	36,3	155	69	378	427	482	46
450	70.012.9450.11	450X40,9 SDR11 ISO S-5	13.700	450	40,9	166	63	440	514	585	60
500	70.012.9500.11	500X45,4 SDR11 ISO S-5	13.600	500	45,4	175	70	480	530	585	60