



Reducer concentric short spigot
machined Butt-welding PE 100-RC black

| Size | Code | Detail | Weight | da(OD) mm | da1(OD1) mm | s mm | s1 mm | L mm | L1 mm | L2 mm |
|---------|----------------|-----------------------------|--------|--------------|----------------|---------|----------|---------|----------|----------|
| 355/200 | 70.317.3520.11 | 355/200 SDR11 ISO S-5 | 5.200 | 355 | 200 | 32,2 | 18,2 | 145 | 49 | 40 |
| 355/225 | 70.317.3522.11 | 355/225 SDR11 ISO S-5 | 4.600 | 355 | 225 | 32,2 | 20,5 | 135 | 46 | 40 |
| 355/250 | 70.317.3525.11 | 355/250 SDR11 ISO S-5 | 3.700 | 355 | 250 | 32,2 | 22,7 | 125 | 43 | 40 |
| 355/280 | 70.317.3528.11 | 355/280 SDR11 ISO S-5 | 4.000 | 355 | 280 | 32,2 | 25,4 | 115 | 42 | 40 |
| 355/315 | 70.317.3531.11 | 355/315 SDR11 ISO S-5 | 3.300 | 355 | 315 | 32,2 | 28,6 | 100 | 37 | 40 |
| 400/250 | 70.317.4025.11 | 400/250 SDR11 ISO S-5 | 5.700 | 400 | 250 | 36,3 | 22,7 | 145 | 50 | 40 |
| 400/280 | 70.317.4028.11 | 400/280 SDR11 ISO S-5 | 6.200 | 400 | 280 | 36,3 | 25,4 | 130 | 44 | 40 |
| 400/315 | 70.317.4031.11 | 400/315 SDR11 ISO S-5 | 6.200 | 400 | 315 | 36,3 | 28,6 | 125 | 49 | 40 |



| Size | Code | Detail | Weight | da(OD) mm | da1(OD1) mm | s mm | s1 mm | L mm | L1 mm | L2 mm |
|---------|----------------|-----------------------------|--------|--------------|----------------|---------|----------|---------|----------|----------|
| 400/355 | 70.317.4035.11 | 400/355 SDR11 ISO S-5 | 4.600 | 400 | 355 | 36,3 | 32,2 | 110 | 45 | 40 |
| 450/315 | 70.317.4531.11 | 450/315 SDR11 ISO S-5 | 6.800 | 450 | 315 | 40,9 | 28,6 | 145 | 54 | 40 |
| 450/355 | 70.317.4535.11 | 450/355 SDR11 ISO S-5 | 7.800 | 450 | 355 | 40,9 | 32,2 | 130 | 51 | 40 |
| 450/400 | 70.317.4540.11 | 450/400 SDR11 ISO S-5 | 5.900 | 450 | 400 | 40,9 | 36,3 | 110 | 44 | 40 |
| 500/280 | 70.317.5028.11 | 500/280 SDR11 ISO S-5 | 11.300 | 500 | 280 | 45,4 | 25,4 | 180 | 65 | 40 |
| 500/315 | 70.317.5031.11 | 500/315 SDR11 ISO S-5 | 10.300 | 500 | 315 | 45,4 | 28,6 | 165 | 60 | 40 |
| 500/355 | 70.317.5035.11 | 500/355 SDR11 ISO S-5 | 9.831 | 500 | 355 | 45,4 | 32,2 | 150 | 57 | 40 |
| 500/400 | 70.317.5040.11 | 500/400 SDR11 ISO S-5 | 8.800 | 500 | 400 | 45,4 | 36,3 | 135 | 55 | 40 |
| 500/450 | 70.317.5045.11 | 500/450 SDR11 ISO S-5 | 8.300 | 500 | 450 | 45,4 | 40,9 | 120 | 54 | 40 |
| 560/225 | 70.317.5622.11 | 560/225 SDR11 ISO S-5 | 10.500 | 560 | 225 | 50,8 | 20,5 | 240 | 92 | 40 |
| 560/450 | 70.317.5645.11 | 560/450 SDR11 ISO S-5 | 13.000 | 560 | 450 | 50,8 | 40,9 | 145 | 62 | 40 |
| 560/500 | 70.317.5650.11 | 560/500 SDR11 ISO S-5 | 11.000 | 560 | 500 | 50,8 | 45,4 | 130 | 61 | 40 |



| Size | Code | Detail | Weight | da(OD) mm | da1(OD1) mm | s mm | s1 mm | L mm | L1 mm | L2 mm |
|---------|----------------|-----------------------------|--------|--------------|----------------|---------|----------|---------|----------|----------|
| 630/315 | 70.317.6331.11 | 630/315 SDR11 ISO S-5 | 22.100 | 630 | 315 | 57,2 | 28,6 | 220 | 78 | 40 |
| 630/400 | 70.317.6340.11 | 630/400 SDR11 ISO S-5 | 20.600 | 630 | 400 | 57,2 | 36,3 | 190 | 72 | 40 |
| 630/450 | 70.317.6345.11 | 630/450 SDR11 ISO S-5 | 19.300 | 630 | 450 | 57,2 | 40,9 | 175 | 71 | 40 |
| 630/500 | 70.317.6350.11 | 630/500 SDR11 ISO S-5 | 19.000 | 630 | 500 | 57,2 | 45,4 | 160 | 71 | 40 |
| 630/560 | 70.317.6356.11 | 630/560 SDR11 ISO S-5 | 14.800 | 630 | 560 | 57,2 | 50,8 | 140 | 68 | 40 |