



Pipe black 12m FM 1613 approved 215  
psi / 15 bar extruded PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	s mm
63	70.722.0063.11	63X5,8 SDR11 ISO-S5	1.060	63	5,8
75	70.722.0075.11	75X6,8 SDR11 ISO-S5	1.480	75	6,8
90	70.722.0090.11	90X8,2 SDR11 ISO-S5	2.125	90	8,2
110	70.722.0110.11	110X10,0 SDR11 ISO-S5	3.167	110	10
125	70.722.0125.11	125X11,4 SDR11 ISO-S5	4.118	125	11,4
140	70.722.0140.11	140X12,7 SDR11 ISO-S5	5.130	140	12,7
160	70.722.0160.11	160X14,6 SDR11 ISO-S5	6.740	160	14,6
180	70.722.0180.11	180X16,4 SDR11 ISO-S5	8.509	180	16,4
200	70.722.0200.11	200X18,2 SDR11 ISO-S5	10.500	200	18,2
225	70.722.0225.11	225X20,5 SDR11 ISO-S5	13.300	225	20,5
250	70.722.0250.11	250X22,7 SDR11 ISO-S5	16.299	250	22,7
280	70.722.0280.11	280X25,4 SDR11 ISO-S5	20.500	280	25,4
315	70.722.0315.11	315X28,6 SDR11 ISO-S5	25.900	315	28,6
355	70.722.0355.11	355X32,2 SDR11 ISO-S5	32.901	355	32,2
400	70.722.0400.11	400X36,3 SDR11 ISO-S5	41.700	400	36,3
450	70.722.0450.11	450X40,9 SDR11 ISO S-5	52.800	450	40,9
500	70.722.0500.11	500X45,4 SDR11 ISO S-5	65.200	500	45,4
560	70.722.0560.11	560X50,8 SDR11 ISO S-5	81.700	560	50,8
630	70.722.0630.11	630X57,2 SDR11 ISO S-5	103.000	630	57,2