



Reducer concentric long spigot W/P-TW  
injection moulded+chamfered Butt + E-  
fusion-welding PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
110/63	70.067.1163.09	110/63 SDR9 PN20	0.581	110	63	12,3	7,1	178	80	59
110/90	70.067.1190.09	110/90 SDR9 PN20	0.650	110	90	12,3	10,1	178	80	75
125/63	70.067.1263.09	125/63 SDR9 PN20	0.767	125	63	14	7,1	190	85	62
125/90	70.067.1290.09	125/90 SDR9 PN20	0.808	125	90	14	10,1	189	85,5	76
125/110	70.067.1211.09	125/110 SDR9 PN20	0.950	125	110	14	12,9	197,5	87	86
160/90	70.067.1690.09	160/90 SDR9 PN20	1.431	160	90	17,9	10,1	216	89	77
160/110	70.067.1611.09	160/110 SDR9 PN20	1.520	160	110	17,9	12,3	223	89	86
160/125	70.067.1612.09	160/125 SDR9 PN20	1.700	160	125	17,9	14	228	93	90
200/160	70.067.2016.09	200/160 SDR9 PN20	2.960	200	160	22,4	17,9	251	98	107



Size	Code	Detail	Weight	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
225/160	70.067.2216.09	225/160 SDR9 PN20	3.600	225	160	30,8	21,9	268	120	104
250/160	70.067.2516.09	250/160 SDR9 PN20	5.450	250	160	27,9	17,9	314	152,5	112
250/225	70.067.2522.09	250/225 SDR9 PN20	3.860	250	225	27,9	25,2	312	152,5	130,5