



High pressure flange ANSI PN20 incl. sealing + backing ring and centerring drilled ANSI CL150 Butt-welding PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d mm	d2 mm	d4 mm	h mm
63	70.294.0063.09	63x7,1 SDR9 ISO S-4	2.210	63	7,1	95	60,5	150	19	100,4	17
75	70.294.0075.09	75x8,4 SDR9 ISO S-4	3.420	75	8,4	105	64,3	180	19	117	20
90	70.294.0090.09	90x10,1 SDR9 ISO S-4	4.000	90	10,1	105	61,7	190	19	132,4	21
110	70.294.0110.09	110x12,3 SDR9 ISO S-4	6.000	110	12,3	105	60,7	230	19	170,5	22
125	70.294.0125.09	125x14,0 SDR9 ISO S-4	5.220	125	14	115	62,7	230	19	170,5	30
140	70.294.0140.09	140x15,7 SDR9 ISO S-4	6.540	140	15,7	115	62,7	255	22,5	188,4	30
160	70.294.0160.09	160x17,9 SDR9 ISO S-4	8.900	160	17,9	115	61,1	280	22,5	219,6	30
180	70.294.0180.09	180x20,1 SDR9 ISO S-4	7.330	180	20,1	115	61,1	280	22,5	219,6	30



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d mm	d2 mm	d4 mm	h mm
200	70.294.0200.09	200x22,4 SDR9 ISO S-4	15.500	200	22,4	130	64	345	22,5	276,5	39
225	70.294.0225.09	225x25,2 SDR9 ISO S-4	13.600	225	25,2	130	64	345	22,5	276,5	39
250	70.294.0250.09	250x27,9 SDR9 ISO S-4	22.500	250	27,9	140	61,4	405	25,5	337	50
280	70.294.0280.09	280x31,3 SDR9 ISO S-4	18.800	280	31,3	140	61,4	405	25,5	337	50
315	70.294.0315.09	315x35,2 SDR9 ISO S-4	33.400	315	35,2	190	102,8	485	25,5	406	57
355	70.294.0355.09	355x39,7 SDR9 ISO S-4	42.500	355	39,7	200	103,6	535	29	445	63
400	70.294.0400.09	400x44,7 SDR9 ISO S-4	54.800	400	44,7	205	100	595	29	510	70
450	70.294.0450.09	450x50,3 SDR9 ISO S-4	61.670	450	50,3	225	103,9	635	32	545	83
500	70.294.0500.09	500x55,8 SDR9 ISO S-4	78.630	500	55,8	230	102,7	700	32	600	86
560	70.294.0560.09	560x62,5 SDR9 ISO S-4	86.300	560	62,5	235	100,5	750	35	655	90
630	70.294.0630.09	630x70 SDR9 ISO S-4	102.000	630	70,3	237	100,9	815	35	709	90