



Pipe black 12m FM 1613 approved 250 psi / 17,5 bar extruded PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	s mm
63	70.722.0063.09	63X7,1 SDR9 ISO-S4	1.300	63	7,1
75	70.722.0075.09	75x8,4 SDR9 ISO-S4	1.800	75	8,4
90	70.722.0090.09	90x10,1 SDR9 ISO-S4	2.600	90	10,1
110	70.722.0110.09	110x12,3 SDR9 ISO-S4	3.800	110	12,3
125	70.722.0125.09	125x14 SDR9 ISO-S4	4.900	125	14
140	70.722.0140.09	140x15,7 SDR9 ISO-S4	6.200	140	15,7
160	70.722.0160.09	160x17,9 SDR9 ISO-S4	8.040	160	17,9
180	70.722.0180.09	180x20,1 SDR9 ISO-S4	10.200	180	20,1
200	70.722.0200.09	200x22,4 SDR9 ISO-S4	12.600	200	22,4
225	70.722.0225.09	225x25,2 SDR9 ISO-S4	15.900	225	25,2
250	70.722.0250.09	250x27,9 SDR9 ISO-S4	19.560	250	27,9
280	70.722.0280.09	280x31,3 SDR9 ISO-S4	24.600	280	31,3
315	70.722.0315.09	315x35,2 SDR9 ISO-S4	31.100	315	35,2
355	70.722.0355.09	355x39,7 SDR9 ISO-S4	39.500	355	39,7
400	70.722.0400.09	400x44,7 SDR9 ISO-S4	50.100	400	44,7
450	70.722.0450.09	450x50,3 SDR9 ISO-S4	63.400	450	50,3
500	70.722.0500.09	500x55,8 SDR9 ISO-S4	78.100	500	55,8
560	70.722.0560.09	560x62,5 SDR9 ISO-S4	98.000	560	62,5
630	70.722.0630.09	630x70,3 SDR9 ISO-S4	124.000	630	70,3