



Sweep Bend  $22^\circ$  radius  $1.5 \times OD$  formed out of pipe Butt + E-fusion-welding PE 100-RC black

Size	Code	Detail	Weight	da(OD) mm	s mm	r mm	z mm	L mm
90	70.395.0090.09	90 SDR9 ISO S-4 20 bar	1.700	90	10,1	135	210	150
110	70.395.0110.09	110 SDR9 ISO S-4 20 bar	2.480	110	12,3	165	330	150
125	70.395.0125.09	125 SDR9 ISO S-4 20 bar	3.670	125	14	188	240	150
140	70.395.0140.09	140 SDR9 ISO S-4 20 bar	4.750	140	15,7	210	250	150
160	70.395.0160.09	160 SDR9 ISO S-4 20 bar	6.790	160	17,9	240	420	150
180	70.395.0180.09	180 SDR9 ISO S-4 20 bar	8.990	180	20,1	270	280	150
200	70.395.0200.09	200 SDR9 ISO S-4 20 bar	12.200	200	22,4	300	290	150
225	70.395.0225.09	225 SDR9 ISO S-4 20 bar	16.000	225	25,2	338	510	150
250	70.395.0250.09	250 SDR9 ISO S-4 20 bar	21.190	250	27,9	375	450	250
280	70.395.0280.09	280 SDR9 ISO S-4 20 bar	26.640	280	31,3	420	460	250
315	70.395.0315.09	315 SDR9 ISO S-4 20 bar	39.000	315	35,2	473	700	450



Size	Code	Detail	Weight	da(OD) mm	s mm	r mm	z mm	L mm
355	70.395.0355.09	355 SDR9 ISO S-4 20 bar	55.300	355	39,7	560	580	300
400	70.395.0400.09	400 SDR9 ISO S-4 20 bar	66.200	400	44,7	637	600	300
450	70.395.0450.09	450 SDR9 ISO S-4 20 bar	83.690	450	50,3	711	620	300
500	70.395.0500.09	500 SDR9 ISO S-4 20 bar	117.000	500	55,8	783	650	350
560	70.395.0560.09	560 SDR9 ISO S-4 20 bar	150.000	560	62,5	877	850	350
630	70.395.0630.09	630 SDR9 ISO S-4 20 bar	200.000	630	62,5	955	850	350