



Drainage Pipe 12m fully perforated
extruded+drilled PE 100 black

| Size | Code | Detail | Weight | da(OD) mm | s mm | L3 mm |
|------|----------------|------------------------|--------|--------------|------|-------|
| 110 | 25.731.0110.17 | 110X6,6 SDR17 ISO S-8 | 2.190 | 110 | 6,6 | 58 |
| 125 | 25.731.0125.17 | 125X7,4 SDR17 ISO S-8 | 2.790 | 125 | 7,4 | 70 |
| 140 | 25.731.0140.17 | 140X8,3 SDR17 ISO S-8 | 3.500 | 140 | 8,3 | 67 |
| 160 | 25.731.0160.17 | 160X9,5 SDR17 ISO S-8 | 4.570 | 160 | 9,5 | 64 |
| 180 | 25.731.0180.17 | 180X10,7 SDR17 ISO S-8 | 5.770 | 180 | 10,7 | 83 |
| 200 | 25.731.0200.17 | 200X11,9 SDR17 ISO S-8 | 7.120 | 200 | 11,9 | 77 |
| 225 | 25.731.0225.17 | 225X13,4 SDR17 ISO S-8 | 9.030 | 225 | 13,4 | 74 |
| 250 | 25.731.0250.17 | 250X14,8 SDR17 ISO S-8 | 11.100 | 250 | 14,8 | 71 |
| 280 | 25.731.0280.17 | 280X16,6 SDR17 ISO S-8 | 13.900 | 280 | 16,6 | 67 |
| 315 | 25.731.0315.17 | 315X18,7 SDR17 ISO S-8 | 17.600 | 315 | 18,7 | 93 |
| 355 | 25.731.0355.17 | 355X21,1 SDR17 ISO S-8 | 22.400 | 355 | 21,1 | 87 |
| 63 | 25.731.0063.11 | 63X5,8 SDR11 ISO S-5 | 1.060 | 63 | 5,8 | 58 |
| 75 | 25.731.0075.11 | 75X6,8 SDR11 ISO S-5 | 1.480 | 75 | 6,8 | 76 |
| 90 | 25.731.0090.11 | 90X8,2 SDR11 ISO S-5 | 2.140 | 90 | 8,2 | 71 |
| 110 | 25.731.0110.11 | 110X10,0 SDR11 ISO S-5 | 3.180 | 110 | 10 | 58 |
| 125 | 25.731.0125.11 | 125X11,4 SDR11 ISO S-5 | 4.120 | 125 | 11,4 | 70 |
| 140 | 25.731.0140.11 | 140X12,7 SDR11 ISO S-5 | 5.130 | 140 | 12,7 | 67 |
| 160 | 25.731.0160.11 | 160X14,6 SDR11 ISO S-5 | 6.740 | 160 | 14,6 | 64 |
| 180 | 25.731.0180.11 | 180X16,4 SDR11 ISO S-5 | 8.510 | 180 | 16,4 | 83 |



| Size | Code | Detail | Weight | da(OD) mm | s mm | L3 mm |
|------|----------------|---------------------------|--------|--------------|------|-------|
| 200 | 25.731.0200.11 | 200X18,2 SDR11 ISO S-5 | 10.500 | 200 | 18,2 | 77 |
| 225 | 25.731.0225.11 | 225X20,5 SDR11 ISO S-5 | 13.300 | 225 | 20,5 | 74 |
| 250 | 25.731.0250.11 | 250X22,7 SDR11 ISO S-5 | 16.300 | 250 | 22,7 | 71 |
| 280 | 25.731.0280.11 | 280X25,4 SDR11 ISO S-5 | 20.500 | 280 | 25,4 | 67 |
| 315 | 25.731.0315.11 | 315X28,6 SDR11 ISO S-5 | 25.900 | 315 | 28,6 | 93 |
| 355 | 25.731.0355.11 | 355X32,2 SDR11 ISO S-5 | 32.900 | 355 | 32,2 | 87 |
| 63 | 25.731.0063.07 | 63X8,6 SDR7,4 ISO S-3,2 | 1.490 | 63 | 8,6 | 58 |
| 75 | 25.731.0075.07 | 75X10,3 SDR7,4 ISO S-3,2 | 2.090 | 75 | 10,3 | 76 |
| 90 | 25.731.0090.07 | 90X12,3 SDR7,4 ISO S-3,2 | 3.030 | 90 | 12,3 | 71 |
| 110 | 25.731.0110.07 | 110X15,1 SDR7,4 ISO S-3,2 | 4.540 | 110 | 15,1 | 58 |
| 125 | 25.731.0125.07 | 125X17,1 SDR7,4 ISO S-3,2 | 5.840 | 125 | 17,1 | 70 |
| 140 | 25.731.0140.07 | 140X19,2 SDR7,4 ISO S-3,2 | 7.330 | 140 | 19,2 | 67 |
| 160 | 25.731.0160.07 | 160X21,9 SDR7,4 ISO S-3,2 | 9.540 | 160 | 21,9 | 64 |
| 180 | 25.731.0180.07 | 180X24,6 SDR7,4 ISO S-3,2 | 12.100 | 180 | 24,6 | 83 |
| 200 | 25.731.0200.07 | 200X27,4 SDR7,4 ISO S-3,2 | 14.900 | 200 | 27,4 | 77 |
| 225 | 25.731.0225.07 | 225X30,8 SDR7,4 ISO S-3,2 | 18.800 | 225 | 30,8 | 74 |
| 250 | 25.731.0250.07 | 250X34,2 SDR7,4 ISO S-3,2 | 23.300 | 250 | 34,2 | 71 |
| 280 | 25.731.0280.07 | 280X38,3 SDR7,4 ISO S-3,2 | 29.200 | 280 | 38,3 | 67 |
| 315 | 25.731.0315.07 | 315X43,1 SDR7,4 ISO S-3,2 | 36.900 | 315 | 43,1 | 93 |
| 355 | 25.731.0355.07 | 355X48,5 SDR7,4 ISO S-3,2 | 46.800 | 355 | 48,5 | 87 |