



Stub Flange DIN short spigot injection
moulded Butt + IR-welding PP Pure grey

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
20	72.012.0020.11	20X1,9 SDR11 ISO S-5	0.015	20	1,9	52	30	27	45	7
25	72.012.0025.11	25X2,3 SDR11 ISO S-5	0.030	25	2,3	52	25	33	58	9
32	72.012.0032.11	32X2,9 SDR11 ISO S-5	0.043	32	2,9	50	25	40	68	10
40	72.012.0040.11	40X3,7 SDR11 ISO S-5	0.062	40	3,7	52	24	50	78	11
50	72.012.0050.11	50X4,6 SDR11 ISO S-5	0.086	50	4,6	53	22	61	88	12
63	72.012.0063.11	63X5,8 SDR11 ISO S-5	0.120	63	5,8	50	20	75	102	14
75	72.012.0075.11	75X6,8 SDR11 ISO S-5	0.187	75	6,8	50,5	18	89	122	16
90	72.012.0090.11	90X8,2 SDR11 ISO S-5	0.327	90	8,2	82	40	105	138	17



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	72.012.0110.11	110X10,0 SDR11 ISO S-5	0.441	110	10	82	38	125	158	18
125	72.012.0125.11	125X11,4 SDR11 ISO S-5	0.488	125	11,4	80	38	132	158	25
140	72.012.0140.11	140X12,7 SDR11 ISO S-5	0.710	140	12,7	92	37	155	188	25
160	72.012.0160.11	160X14,6 SDR11 ISO S-5	0.972	160	14,6	92	38	175	212	25
180	72.012.0180.11	180X16,4 SDR11 ISO S-5	0.994	180	16,4	93	43	183	212	30
200	72.012.0200.11	200X18,2 SDR11 ISO S-5	2.140	200	18,2	114	40	232	268	32
225	72.012.0225.11	225X20,5 SDR11 ISO S-5	2.030	225	20,5	113	52	235	268	32
250	72.012.0250.11	250X22,7 SDR11 ISO S-5	3.400	250	22,7	130	58	285	320	35
280	72.012.0280.11	280X25,4 SDR11 ISO S-5	3.113	280	25,4	128	66	288	320	35
315	72.012.0315.11	315X28,6 SDR11 ISO S-5	4.576	315	28,6	136	65	335	370	35