



Stub Flange ANSI short spigot injection moulded Butt + IR-welding PP Pure grey

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
20	72.012.1020.11	20X1,9 SDR11 ISO S-5	0.015	20	1,9	52	30	27	44,5	7
25	72.012.1025.11	25X2,3 SDR11 ISO S-5	0.031	25	2,3	52	25	33	54,1	9
32	72.012.1032.11	32X2,9 SDR11 ISO S-5	0.037	32	2,9	50	25	40	63,5	10
40	72.012.1040.11	40X3,7 SDR11 ISO S-5	0.048	40	3,7	52	24	50	71,5	11
50	72.012.1050.11	50X4,6 SDR11 ISO S-5	0.081	50	4,6	53	22	61	82,55	12
63	72.012.1063.11	63X5,8 SDR11 ISO S-5	0.119	63	5,8	50	20	75	100,4	14
75	72.012.1075.11	75X6,8 SDR11 ISO S-5	0.171	75	6,8	50,5	18	89	117	16
90	72.012.1090.11	90X8,2 SDR11 ISO S-5	0.307	90	8,2	82	40	105	132,4	17



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	72.012.1110.11	110X10,0 SDR11 ISO S-5	0.446	110	10	82	38	125	158	18
125	72.012.1125.11	125X11,4 SDR11 ISO S-5	0.509	125	11,4	82	38	132	158	25
160	72.012.1160.11	160X14,6 SDR11 ISO S-5	1.020	160	14,6	92	38	175	212	25
200	72.012.1200.11	200X18,2 SDR11 ISO S-5	1.960	200	18,2	114	40	232	268	32
225	72.012.1225.11	225X20,5 SDR11 ISO S-5	1.950	225	20,5	113	52	235	268	32
250	72.012.1250.11	250X22,7 SDR11 ISO S-5	3.380	250	22,7	130	58	285	320	35
315	72.012.1315.11	315X28,6 SDR11 ISO S-5	4.645	315	28,6	136	65	335	370	35