



End Cap long spigot injection moulded
Butt + IR-welding PP Pure grey

| Size | Code | Detail | Weight | da(OD) mm | s mm | L mm | L3 mm |
|------|----------------|------------------------|--------|--------------|------|------|-------|
| 20 | 72.064.0020.11 | 20X1,9 SDR11 ISO S-5 | 0.006 | 20 | 1,9 | 47 | 41 |
| 25 | 72.064.0025.11 | 25X2,3 SDR11 ISO S-5 | 0.011 | 25 | 2,3 | 49 | 41 |
| 32 | 72.064.0032.11 | 32X2,9 SDR11 ISO S-5 | 0.014 | 32 | 2,9 | 56 | 47 |
| 40 | 72.064.0040.11 | 40X3,7 SDR11 ISO S-5 | 0.023 | 40 | 3,7 | 64 | 51 |
| 50 | 72.064.0050.11 | 50X4,6 SDR11 ISO S-5 | 0.048 | 50 | 4,6 | 73 | 60 |
| 63 | 72.064.0063.11 | 63X5,8 SDR11 ISO S-5 | 0.053 | 63 | 5,8 | 84 | 68 |
| 75 | 72.064.0075.11 | 75X6,8 SDR11 ISO S-5 | 0.160 | 75 | 6,8 | 93 | 75 |
| 90 | 72.064.0090.11 | 90X8,2 SDR11 ISO S-5 | 0.236 | 90 | 8,2 | 109 | 84 |
| 110 | 72.064.0110.11 | 110X10,0 SDR11 ISO S-5 | 0.466 | 110 | 10 | 136 | 104 |
| 125 | 72.064.0125.11 | 125X11,4 SDR11 ISO S-5 | 0.607 | 125 | 11,4 | 138 | 102 |
| 140 | 72.064.0140.11 | 140X12,7 SDR11 ISO S-5 | 0.810 | 140 | 12,7 | 144 | 106 |
| 160 | 72.064.0160.11 | 160X14,6 SDR11 ISO S-5 | 1.145 | 160 | 14,6 | 170 | 118,5 |
| 180 | 72.064.0180.11 | 180X16,4 SDR11 ISO S-5 | 1.660 | 180 | 16,4 | 164 | 115 |
| 200 | 72.064.0200.11 | 200X18,2 SDR11 ISO S-5 | 2.060 | 200 | 18,2 | 181 | 127 |
| 225 | 72.064.0225.11 | 225X20,5 SDR11 ISO S-5 | 2.677 | 225 | 20,5 | 202 | 131 |
| 250 | 72.064.0250.11 | 250X22,7 SDR11 ISO S-5 | 3.860 | 250 | 22,7 | 230 | 161 |
| 280 | 72.064.0280.11 | 280X25,4 SDR11 ISO S-5 | 5.240 | 280 | 25,4 | 257 | 162 |
| 315 | 72.064.0315.11 | 315X28,6 SDR11 ISO S-5 | 7.000 | 315 | 28,6 | 272 | 171 |