



Bend 90° short spigot injection moulded  
Butt + IR-welding PVDF UHP natural

Size	Code	Detail	Weight	da(OD) mm	s mm	r mm	z mm
125	35.001.0125.33	125X3,9 SDR33 ISO S-16	0.686	125	3,9	125	135
180	35.001.0180.33	180X5,5 SDR33 ISO S-16	1.891	180	5,5	175	200
200	35.001.0200.33	200X6,2 SDR33 ISO S-16	2.730	200	6,2	196	217
250	35.001.0250.33	250X7,7 SDR33 ISO S-16	5.365	250	7,7	250	287
280	35.001.0280.33	280X8,6 SDR33 ISO S-16	6.821	280	8,6	280	288
315	35.001.0315.33	315X9,7 SDR33 ISO S-16	9.811	315	9,7	300	338
125	35.001.0125.21	125X6,0 SDR21 ISO S-10	0.980	125	6	125	135
180	35.001.0180.21	180X8,6 SDR21 ISO S-10	2.884	180	8,6	175	200
200	35.001.0200.21	200X9,6 SDR21 ISO S-10	3.805	200	9,6	196	217
250	35.001.0250.21	250X11,9 SDR21 ISO S-10	7.916	250	11,9	255	287
280	35.001.0280.21	280X13,4 SDR21 ISO S-10	10.100	280	13,4	260	288
315	35.001.0315.21	315X15,0 SDR21 ISO S-10	14.510	315	15	300	338