



Bend 45° 100mm both sides elongated  
injection moulded+welded Butt + IR-  
welding PVDF UHP natural

| Size | Code           | Detail                  | Weight | da(OD)<br>mm | s mm | L mm | L1<br>mm | L2<br>mm |
|------|----------------|-------------------------|--------|--------------|------|------|----------|----------|
| 125  | 35.001.2125.33 | 125X3,9 SDR33 ISO S-16  | 0.695  | 125          | 3,9  | 100  | 162      | 152      |
| 180  | 35.001.2180.33 | 180X5,5 SDR33 ISO S-16  | 2.150  | 180          | 5,5  | 100  | 197      | 172      |
| 200  | 35.001.2200.33 | 200X6,2 SDR33 ISO S-16  | 2.820  | 200          | 6,2  | 100  | 202      | 181      |
| 225  | 35.001.2225.33 | 225X6,9 SDR33 ISO S-16  | 3.760  | 225          | 6,9  | 100  | 211      | 193      |
| 250  | 35.001.2250.33 | 250X7,7 SDR33 ISO S-16  | 5.118  | 250          | 7,7  | 100  | 241      | 204      |
| 280  | 35.001.2280.33 | 280X8,6 SDR33 ISO S-16  | 6.277  | 280          | 8,6  | 100  | 224      | 216      |
| 315  | 35.001.2315.33 | 315X9,7 SDR33 ISO S-16  | 8.917  | 315          | 9,7  | 100  | 262      | 224      |
| 125  | 35.001.2125.21 | 125X6 SDR21 ISO S-10    | 1.358  | 125          | 6    | 100  | 162      | 152      |
| 180  | 35.001.2180.21 | 180X8,6 SDR21 ISO S-10  | 3.277  | 180          | 8,6  | 100  | 197      | 172      |
| 200  | 35.001.2200.21 | 200X9,6 SDR21 ISO S-10  | 4.050  | 200          | 9,6  | 100  | 202      | 181      |
| 280  | 35.001.2280.21 | 280X13,4 SDR21 ISO S-10 | 9.260  | 280          | 13,4 | 100  | 224      | 216      |