



Tee short spigot injection moulded Butt + IR-welding PVDF UHP natural

Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
90	35.006.0090.33	90X2,8 SDR33 ISO S-16	0.469	90	2,8	92	185	33,5
110	35.006.0110.33	110X3,4 SDR33 ISO S-16	0.866	110	3,4	110	221	33,5
125	35.006.0125.33	125X3,9 SDR33 ISO S-16	1.245	125	3,9	139	279	52
140	35.006.0140.33	140X4,3 SDR33 ISO S-16	1.715	140	4,3	154	308	60
160	35.006.0160.33	160X4,9 SDR33 ISO S-16	1.940	160	4,9	140	279	45
180	35.006.0180.33	180X5,5 SDR33 ISO S-16	3.410	180	5,5	200	400	80
200	35.006.0200.33	200X6,2 SDR33 ISO S-16	5.560	200	6,2	223	446	89
225	35.006.0225.33	225X6,9 SDR33 ISO S-16	6.953	225	6,9	246	496	99
250	35.006.0250.33	250X7,7 SDR33 ISO S-16	8.405	250	7,7	250	496	80
280	35.006.0280.33	280X8,6 SDR33 ISO S-16	9.989	280	8,6	248	495	70
315	35.006.0315.33	315X9,7 SDR33 ISO S-16	12.320	315	9,7	247	496	57



Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
20	35.006.0020.21	20X1,9 SDR21 ISO S-10	0.022	20	1,9	38	75	25
25	35.006.0025.21	25X1,9 SDR21 ISO S-10	0.032	25	1,9	42	84	25
32	35.006.0032.21	32X2,4 SDR21 ISO S-10	0.059	32	2,4	46	90	25
40	35.006.0040.21	40X2,4 SDR21 ISO S-10	0.096	40	2,4	58	116	31
50	35.006.0050.21	50X3,0 SDR21 ISO S-10	0.147	50	3	64	126	31
63	35.006.0063.21	63X3,0 SDR21 ISO S-10	0.252	63	3	70	140	31
75	35.006.0075.21	75X3,6 SDR21 ISO S-10	0.383	75	3,6	89	178	42
90	35.006.0090.21	90X4,3 SDR21 ISO S-10	0.596	90	4,3	92	185	33,5
110	35.006.0110.21	110X5,3 SDR21 ISO S-10	1.150	110	5,3	110	221	33,5
125	35.006.0125.21	125X6,0 SDR21 ISO S-10	1.575	125	6	139	279	52
140	35.006.0140.21	140X6,7 SDR21 ISO S-10	2.290	140	6,7	154	308	60
160	35.006.0160.21	160X7,7 SDR21 ISO S-10	2.677	160	7,7	140	279	45
180	35.006.0180.21	180X8,6 SDR21 ISO S-10	4.850	180	8,6	200	400	80
200	35.006.0200.21	200X9,6 SDR21 ISO S-10	7.015	200	9,6	223	446	89
225	35.006.0225.21	225X10,8 SDR21 ISO S-10	9.205	225	10,8	246	496	99
250	35.006.0250.21	250X11,9 SDR21 ISO S-10	11.372	250	11,9	250	496	80
280	35.006.0280.21	280X13,4 SDR21 ISO S-10	13.700	280	13,4	248	495	70



Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L mm	L3 mm
315	35.006.0315.21	315X15,0 SDR21 ISO S-10	17.065	315	15	247	496	57