



Stub Flange JIS short spigot injection moulded Butt + IR-welding PVDF UHP natural

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
90	35.012.2090.33	90X2,8 SDR33 ISO S-16	0.367	90	2,8	80	42	105	129	11
110	35.012.2110.33	110X3,4 SDR33 ISO S-16	0.463	110	3,4	80	42	125	154	12
125	35.012.2125.33	125X3,9 SDR33 ISO S-16	0.475	125	3,9	80	33	132	154	14
140	35.012.2140.33	140X4,3 SDR33 ISO S-16	0.636	140	4,3	80	41	155	185	15
160	35.012.2160.33	160X4,9 SDR33 ISO S-16	0.919	160	4,9	81	37	175	212	16
200	35.012.2200.33	200X6,2 SDR33 ISO S-16	1.940	200	6,2	98	42	232	265	18
225	35.012.2225.33	225X6,9 SDR33 ISO S-16	1.412	225	6,9	100	76	235	265	18
250	35.012.2250.33	250X7,7 SDR33 ISO S-16	2.770	250	7,7	100	40	285	320	20



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
280	35.012.2280.33	280X8,6 SDR33 ISO S-16	2.104	280	8,6	100	50	288	320	20
20	35.012.2020.21	20X1,9 SDR21 ISO S-10	0.029	20	1,9	49	31	27	45	6
25	35.012.2025.21	25X1,9 SDR21 ISO S-10	0.044	25	1,9	50	30	33	58	6,5
32	35.012.2032.21	32X2,4 SDR21 ISO S-10	0.066	32	2,4	50	26	40	68	7
40	35.012.2040.21	40X2,4 SDR21 ISO S-10	0.097	40	2,4	50	24	50	78	8
50	35.012.2050.21	50X3,0 SDR21 ISO S-10	0.128	50	3	50	22	61	84	9
63	35.012.2063.21	63X3,0 SDR21 ISO S-10	0.174	63	3	50	19,5	76	99	10
75	35.012.2075.21	75X3,6 SDR21 ISO S-10	0.236	75	3,6	50	20	89	119	10
90	35.012.2090.21	90X4,3 SDR21 ISO S-10	0.369	90	4,3	80	42	105	129	11
110	35.012.2110.21	110X5,3 SDR21 ISO S-10	0.521	110	5,3	80	40	125	154	12
125	35.012.2125.21	125X6,0 SDR21 ISO S-10	0.595	125	6	80	42	132	154	14
140	35.012.2140.21	140X6,7 SDR21 ISO S-10	0.765	140	6,7	80	42	155	185	15



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
160	35.012.2160.21	160X7,7 SDR21 ISO S-10	1.071	160	7,7	81	36,5	175	212	16
180	35.012.2180.21	180X8,6 SDR21 ISO S-10	1.069	180	8,6	80	57	183	212	18
200	35.012.2200.21	200X9,6 SDR21 ISO S-10	2.436	200	9,6	98	43	232	265	20
225	35.012.2225.21	225X10,8 SDR21 ISO S-10	1.881	225	10,8	100	76	235	265	20
250	35.012.2250.21	250X11,9 SDR21 ISO S-10	3.550	250	11,9	97	35	285	320	22
280	35.012.2280.21	280X13,4 SDR21 ISO S-10	2.993	280	13,4	100	72	288	320	25
315	35.012.2315.21	315X15,0 SDR21 ISO S-10	4.280	315	15	100	41	335	370	25