



Restrained Fitting injection moulded Butt  
+ IR-welding PVDF UHP natural

Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L1 mm	L2 mm	d1 mm
90	35.028.0090.33	90X2,8 SDR33 ISO S-16	0.341	90	2,8	150	75	40,5	104
110	35.028.0110.33	110X3,4 SDR33 ISO S-16	0.524	110	3,4	150	77	41	126
125	35.028.0125.33	125X3,9 SDR33 ISO S-16	0.587	125	3,9	160	98	60,5	143
140	35.028.0140.33	140X4,3 SDR33 ISO S-16	0.840	140	4,3	159	100	60,5	159
160	35.028.0160.33	160X4,9 SDR33 ISO S-16	1.040	160	4,9	160	100	60	180
32	35.028.0032.21	32X2,4 SDR21 ISO S-10	0.057	32	2,4	120	70	31,5	40,5
63	35.028.0063.21	63X3,0 SDR21 ISO S-10	0.197	63	3	120	68	30,5	71
90	35.028.0090.21	90X4,3 SDR21 ISO S-10	0.437	90	4,3	150	75	40,5	104
110	35.028.0110.21	110X5,3 SDR21 ISO S-10	0.660	110	5,3	150	77	41	126



Size	Code	Detail	Weight	da(OD) mm	s mm	L mm	L1 mm	L2 mm	d1 mm
125	35.028.0125.21	125X6,0 SDR21 ISO S-10	0.840	125	6	160	98	60,5	143
140	35.028.0140.21	140X6,7 SDR21 ISO S-10	1.100	140	6,7	159	100	60,5	159
160	35.028.0160.21	160X7,7 SDR21 ISO S-10	1.410	160	7,7	158	99,5	60	178,5