



Elbow 45° long spigot injection moulded
Butt + IR-welding PVDF UHP natural

Size	Code	Detail	Weight	da(OD) mm	s mm	z mm	L3 mm
90	35.060.0090.33	90X2,8 SDR33 ISO S-16	0.174	90	2,8	59	36
110	35.060.0110.33	110X3,4 SDR33 ISO S-16	0.309	110	3,4	68	45
140	35.060.0140.33	140X4,3 SDR33 ISO S-16	0.638	140	4,3	85	57
160	35.060.0160.33	160X4,9 SDR33 ISO S-16	0.940	160	4,9	103	65
225	35.060.0225.33	225X6,9 SDR33 ISO S-16	2.245	225	6,9	127,5	75
250	35.060.0250.33	250X7,7 SDR33 ISO S-16	2.878	250	7,7	132	75
20	35.060.0020.21	20X1,9 SDR21 ISO S-10	0.019	20	1,9	43	39
25	35.060.0025.21	25X1,9 SDR21 ISO S-10	0.029	25	1,9	45	40
32	35.060.0032.21	32X2,4 SDR21 ISO S-10	0.052	32	2,4	52	46
40	35.060.0040.21	40X2,4 SDR21 ISO S-10	0.069	40	2,4	58	50
50	35.060.0050.21	50X3,0 SDR21 ISO S-10	0.117	50	3	66	56
63	35.060.0063.21	63X3,0 SDR21 ISO S-10	0.179	63	3	75	62
75	35.060.0075.21	75X3,6 SDR21 ISO S-10	0.151	75	3,6	50	32
90	35.060.0090.21	90X4,3 SDR21 ISO S-10	0.240	90	4,3	59	36
110	35.060.0110.21	110X5,3 SDR21 ISO S-10	0.458	110	5,3	68	45
140	35.060.0140.21	140X6,7 SDR21 ISO S-10	0.956	140	6,7	85	57
160	35.060.0160.21	160X7,7 SDR21 ISO S-10	1.389	160	7,7	103	65
225	35.060.0225.21	225X10,8 SDR21 ISO S-10	3.398	225	10,8	127,5	75
250	35.060.0250.21	250X11,9 SDR21 ISO S-10	4.349	250	11,9	132	75