



Reducer concentric long spigot injection moulded Butt + IR-welding PVDF UHP natural

| Size | Code | Detail | Weight | da(OD) mm | da1(OD1) mm | s mm | s1 mm | L mm | L1 mm | L2 mm |
|---------|----------------|------------------------------|--------|--------------|----------------|---------|----------|---------|----------|----------|
| 110/90 | 35.067.1190.33 | 110/90 SDR33 ISO S-16 | 0.197 | 110 | 90 | 3,4 | 2,8 | 90 | 30 | 35 |
| 140/110 | 35.067.1411.33 | 140/110 SDR33 ISO S-16 | 0.423 | 140 | 110 | 4,3 | 3,4 | 110 | 42 | 40 |
| 160/110 | 35.067.1611.33 | 160/110 SDR33 ISO S-16 | 0.437 | 160 | 110 | 4,9 | 3,4 | 120 | 40 | 35 |
| 160/140 | 35.067.1614.33 | 160/140 SDR33 ISO S-16 | 0.914 | 160 | 140 | 4,9 | 4,3 | 121 | 40 | 35 |
| 225/160 | 35.067.2216.33 | 225/160 SDR33 ISO S-16 | 1.196 | 225 | 160 | 6,9 | 4,9 | 160 | 32 | 35 |
| 250/160 | 35.067.2516.33 | 250/160 SDR33 ISO S-16 | 1.540 | 250 | 160 | 7,7 | 4,9 | 179 | 36 | 36 |
| 250/225 | 35.067.2522.33 | 250/225 SDR33 ISO S-16 | 1.809 | 250 | 225 | 7,7 | 6,9 | 180 | 43 | 28 |
| 315/160 | 35.067.3116.33 | 315/160 SDR33 ISO S-16 | 2.288 | 315 | 160 | 9,7 | 4,9 | 180 | 42 | 30 |



| Size | Code | Detail | Weight | da(OD) mm | da1(OD1) mm | s mm | s1 mm | L mm | L1 mm | L2 mm |
|---------|----------------|------------------------------|--------|--------------|----------------|---------|----------|---------|----------|----------|
| 315/250 | 35.067.3125.33 | 315/250 SDR33 ISO S-16 | 2.569 | 315 | 250 | 9,7 | 7,7 | 180 | 42 | 37 |
| 25/20 | 35.067.2520.21 | 25/20 SDR21 ISO S-10 | 0.012 | 25 | 20 | 1,9 | 1,9 | 50 | 20 | 20 |
| 32/20 | 35.067.3220.21 | 32/20 SDR21 ISO S-10 | 0.017 | 32 | 20 | 2,4 | 1,9 | 50 | 18,5 | 19 |
| 32/25 | 35.067.3225.21 | 32/25 SDR21 ISO S-10 | 0.024 | 32 | 25 | 2,4 | 1,9 | 50 | 20 | 20 |
| 40/20 | 35.067.4020.21 | 40/20 SDR21 ISO S-10 | 0.022 | 40 | 20 | 2,4 | 1,9 | 55 | 20 | 20 |
| 40/25 | 35.067.4025.21 | 40/25 SDR21 ISO S-10 | 0.021 | 40 | 25 | 2,4 | 1,9 | 55 | 20 | 20 |
| 40/32 | 35.067.4032.21 | 40/32 SDR21 ISO S-10 | 0.026 | 40 | 32 | 2,4 | 2,4 | 55 | 20 | 20 |
| 50/20 | 35.067.5020.21 | 50/20 SDR21 ISO S-10 | 0.036 | 50 | 20 | 3 | 1,9 | 60 | 23 | 20 |
| 50/25 | 35.067.5025.21 | 50/25 SDR21 ISO S-10 | 0.038 | 50 | 25 | 3 | 1,9 | 60 | 24 | 20 |
| 50/32 | 35.067.5032.21 | 50/32 SDR21 ISO S-10 | 0.043 | 50 | 32 | 3 | 2,4 | 60 | 25 | 20 |
| 50/40 | 35.067.5040.21 | 50/40 SDR21 ISO S-10 | 0.049 | 50 | 40 | 3 | 2,4 | 60 | 25 | 22 |
| 63/25 | 35.067.6325.21 | 63/25 SDR21 ISO S-10 | 0.060 | 63 | 25 | 3 | 1,9 | 75 | 25 | 20 |



| Size | Code | Detail | Weight | da(OD) mm | da1(OD1) mm | s mm | s1 mm | L mm | L1 mm | L2 mm |
|--------|----------------|-----------------------------|--------|--------------|----------------|---------|----------|---------|----------|----------|
| 63/32 | 35.067.6332.21 | 63/32 SDR21 ISO S-10 | 0.061 | 63 | 32 | 3 | 2,4 | 65 | 25 | 18 |
| 63/40 | 35.067.6340.21 | 63/40 SDR21 ISO S-10 | 0.061 | 63 | 40 | 3 | 2,4 | 65 | 26 | 22 |
| 63/50 | 35.067.6350.21 | 63/50 SDR21 ISO S-10 | 0.068 | 63 | 50 | 3 | 3 | 65 | 25 | 24 |
| 75/40 | 35.067.7540.21 | 75/40 SDR21 ISO S-10 | 0.095 | 75 | 40 | 3,6 | 2,4 | 80 | 34 | 21 |
| 75/50 | 35.067.7550.21 | 75/50 SDR21 ISO S-10 | 0.104 | 75 | 50 | 3,6 | 3 | 80 | 34 | 21 |
| 75/63 | 35.067.7563.21 | 75/63 SDR21 ISO S-10 | 0.110 | 75 | 63 | 3,6 | 3 | 80 | 34 | 21 |
| 90/50 | 35.067.9050.21 | 90/50 SDR21 ISO S-10 | 0.143 | 90 | 50 | 4,3 | 3 | 80 | 34 | 21 |
| 90/63 | 35.067.9063.21 | 90/63 SDR21 ISO S-10 | 0.147 | 90 | 63 | 4,3 | 3 | 80 | 34 | 21 |
| 90/75 | 35.067.9075.21 | 90/75 SDR21 ISO S-10 | 0.156 | 90 | 75 | 4,3 | 3,6 | 80 | 34 | 34 |
| 110/63 | 35.067.1163.21 | 110/63 SDR21 ISO S-10 | 0.241 | 110 | 63 | 5,3 | 3 | 103 | 30 | 33 |
| 110/75 | 35.067.1175.21 | 110/75 SDR21 ISO S-10 | 0.260 | 110 | 75 | 5,3 | 3,6 | 95 | 33 | 33 |
| 110/90 | 35.067.1190.21 | 110/90 SDR21 ISO S-10 | 0.254 | 110 | 90 | 5,3 | 4,3 | 90 | 30 | 35 |



| Size | Code | Detail | Weight | da(OD) mm | da1(OD1) mm | s mm | s1 mm | L mm | L1 mm | L2 mm |
|---------|----------------|-------------------------------------|--------|--------------|----------------|---------|----------|---------|----------|----------|
| 140/63 | 35.067.1463.21 | 140/63 SDR21 ISO S-10 | 0.503 | 140 | 63 | 6,7 | 3 | 133 | 38 | 27 |
| 140/110 | 35.067.1411.21 | 140/110 SDR21 ISO S-10 | 0.502 | 140 | 110 | 6,7 | 5,3 | 110 | 42 | 40 |
| 160/110 | 35.067.1611.21 | 160/110 SDR21 ISO S-10 | 0.654 | 160 | 110 | 7,7 | 5,3 | 120 | 40 | 35 |
| 160/140 | 35.067.1614.21 | 160/140 SDR21 ISO S-10 | 1.434 | 160 | 140 | 7,7 | 6,7 | 121 | 40 | 35 |
| 225/160 | 35.067.2216.21 | 225/160 SDR21 ISO S-10 | 1.690 | 225 | 160 | 10,8 | 7,7 | 160 | 32 | 35 |
| 250/160 | 35.067.2516.21 | 250/160 SDR21 ISO S-10 | 2.237 | 250 | 160 | 11,9 | 7,7 | 179 | 36 | 36 |
| 250/225 | 35.067.2522.21 | 250/225 SDR21 ISO S-10 | 2.678 | 250 | 225 | 11,9 | 10,8 | 180 | 43 | 28 |
| 90/63 | 35.067.9063.31 | 90/63 SDR33/21 MOP 10 bar | 0.139 | 90 | 63 | 2,8 | 3 | 80 | 34 | 21 |
| 110/63 | 35.067.1163.31 | 110/63 SDR33/21 MOP 10 bar | 0.178 | 110 | 63 | 3,4 | 3 | 103 | 30 | 33 |
| 140/63 | 35.067.1463.31 | 140/63 SDR33/21 MOP 10 bar | 0.351 | 140 | 63 | 4,3 | 3 | 133 | 38 | 27 |
| 160/63 | 35.067.1663.31 | 160/63 SDR33/21 MOP 10 bar | 0.514 | 160 | 63 | 4,9 | 3 | 150 | 38 | 27 |



| Size | Code | Detail | Weight | da(OD) mm | da1(OD1) mm | s mm | s1 mm | L mm | L1 mm | L2 mm |
|---------|----------------|--------------------------------------|--------|--------------|----------------|---------|----------|---------|----------|----------|
| 160/110 | 35.067.1611.31 | 160/110 SDR33/21 MOP 10 bar | 1.164 | 160 | 110 | 4,9 | 5,3 | 120 | 40 | 35 |
| 225/110 | 35.067.2211.31 | 225/110 SDR33/21 MOP 10 bar | 1.223 | 225 | 110 | 6,9 | 5,3 | 160 | 30 | 20 |