



Köpek Kemiği Tip III-A, Yaka Tek boruya bağlantılı işlenmiş Kademeli+E-füzyon kaynağı HDPE/PVDF

| Boyut | Kod | Detay | Ağırlık | s1 mm | s2 mm | L mm | d mm | d1 mm | d2 mm | d3 mm | d4 mm |
|---------|----------------|---------------------|---------|----------|----------|---------|---------|----------|----------|----------|----------|
| 90/32 | 84.238.9032.72 | 90/32 SDR17/21 | 3.635 | 5,4 | 2,4 | 300 | 202 | 90 | 32 | 108 | 77 |
| 125/63 | 84.238.1263.72 | 125/63 SDR17/21 | 4.795 | 7,4 | 3 | 344 | 220 | 125 | 63 | 135 | 78 |
| 160/90 | 84.238.1690.73 | 160/90 SDR17/33 | 9.470 | 9,5 | 2,8 | 375 | 287 | 160 | 90 | 178 | 86 |
| 200/110 | 84.238.2011.73 | 200/110 SDR17/33 | 12.124 | 11,9 | 3,4 | 420 | 341 | 200 | 110 | 235 | 92 |
| 280/160 | 84.238.2816.73 | 280/160 SDR17/33 | 23.970 | 16,6 | 4,9 | 468 | 409 | 280 | 160 | 294 | 105 |