



Kör Flanş DIN çelik uç enjeksiyon kalıplı+delikli PN10/16 Flanş bağlantısı
PP-FRP siyah

Teknik katalogda belirtilen nm[NM] torkları maksimum değerler olarak kullanılacaktır.

Boyut	Kod	Detay	Ağırlık	da(OD) mm	d mm	d2 mm
20	14.045.0020.11	20 - MOP 16 bar	0.288	20	95	14
25	14.045.0025.11	25 - MOP 16 bar	0.385	25	108	14
32	14.045.0032.11	32 - MOP 16 bar	0.540	32	115	14
40	14.045.0040.11	40 - MOP 16 bar	0.820	40	140	18
50	14.045.0050.11	50 - MOP 16 bar	0.943	50	150	18
63	14.045.0063.11	63 - MOP 16 bar	1.150	63	165	18
75	14.045.0075.11	75 - MOP 16 bar	1.640	75	185,5	18
90	14.045.0090.11	90 - MOP 16 bar	1.960	90	202	18
110/125	14.045.0110.11	110/125 - MOP 16 bar	2.350	110	220	18
140	14.045.0140.11	140 - MOP 16 bar	3.895	140	250	18
160/180	14.045.0160.11	160/180 - MOP 16 bar	4.870	160	285	22