



MULTI-Bend 90° uzun spigot elektriksel olarak iletken enjeksiyon kalıplı Alın + E-füzyon kaynağı PE 100-el siyah

| Boyut | Kod | Detay | Ağırlık | da(OD) mm | s mm | r mm | z mm | L3 mm |
|-------|----------------|---------------------------|---------|--------------|------|------|-------|-------|
| 110 | 28.068.0110.17 | 110X6,6 SDR17 ISO S-8 | 0.872 | 110 | 6,6 | 110 | 192 | 82 |
| 125 | 28.068.0125.17 | 125X7,4 SDR17 ISO S-8 | 1.270 | 125 | 7,4 | 125 | 218 | 92 |
| 160 | 28.068.0160.17 | 160X9,5 SDR17 ISO S-8 | 2.540 | 160 | 9,5 | 160 | 261,5 | 100,5 |
| 32 | 28.068.0032.11 | 32X3,0 SDR11 ISO S-5 | 0.046 | 32 | 3 | 32 | 79 | 47 |
| 40 | 28.068.0040.11 | 40X3,7 SDR11 ISO S-5 | 0.082 | 40 | 3,7 | 40 | 92,5 | 52 |
| 50 | 28.068.0050.11 | 50X4,6 SDR11 ISO S-5 | 0.150 | 50 | 4,6 | 50 | 108,5 | 58,5 |
| 63 | 28.068.0063.11 | 63X5,8 SDR11 ISO S-5 | 0.290 | 63 | 5,8 | 63 | 129,5 | 66,5 |
| 75 | 28.068.0075.11 | 75X6,8 SDR11 ISO S-5 | 0.454 | 75 | 6,8 | 75 | 150 | 75 |
| 90 | 28.068.0090.11 | 90X8,2 SDR11 ISO S-5 | 0.739 | 90 | 8,2 | 90 | 168 | 76 |
| 110 | 28.068.0110.11 | 110X10,0 SDR11 ISO S-5 | 1.264 | 110 | 10 | 110 | 189 | 82 |
| 125 | 28.068.0125.11 | 125X11,4 SDR11 ISO S-5 | 1.850 | 125 | 11,4 | 125 | 218 | 92 |



| Boyut | Kod | Detay | Ağırlık | da(OD) mm | s mm | r mm | z mm | L3 mm |
|-------|----------------|---------------------------|---------|--------------|------|------|-------|-------|
| 160 | 28.068.0160.11 | 160X14,6 SDR11 ISO S-5 | 3.570 | 160 | 14,6 | 160 | 261,5 | 100,5 |