



Kısa DIN flanşlı flanş enjeksiyon kalıplı  
alın kaynaklı PPR gri

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	11.012.0110.33	110X3,4 SDR33 ISO S-16	0.276	110	3,4	80	31	125	158	18
125	11.012.0125.33	125X3,9 SDR33 ISO S-16	0.270	125	3,9	80	38	132	158	18
140	11.012.0140.33	140X4,3 SDR33 ISO S-16	0.410	140	4,3	80	24	155	188	18
160	11.012.0160.33	160X4,9 SDR33 ISO S-16	0.520	160	4,9	80	28,5	175	212	18
180	11.012.0180.33	180X5,5 SDR33 ISO S-16	0.450	180	5,5	95	55	183	212	18
200	11.012.0200.33	200X6,2 SDR33 ISO S-16	1.020	200	6,2	113	53	232	268	18
225	11.012.0225.33	225X6,9 SDR33 ISO S-16	0.820	225	6,9	113	65	235	268	18
250	11.012.0250.33	250X7,7 SDR33 ISO S-16	1.700	250	7,7	132	70	285	320	20



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
280	11.012.0280.33	280X8,6 SDR33 ISO S-16	1.380	280	8,6	128	70	288	320	20
315	11.012.0315.33	315X9,7 SDR33 ISO S-16	2.020	315	9,7	136	68	335	370	20
355	11.012.0355.33	355X10,9 SDR33 ISO S-16	2.850	355	10,9	150	75	373	430	23
400	11.012.0400.33	400X12,3 SDR33 ISO S-16	3.980	400	12,3	155	75	427	482	26
450	11.012.0450.33	450X13,8 SDR33 ISO S-16	7.740	450	13,8	168	73	514	585	33
500	11.012.0500.33	500X15,3 SDR33 ISO S-16	6.960	500	15,3	175	81	530	585	33
560	11.012.0560.33	560X17,2 SDR33 ISO S-16	8.750	560	17,2	120	25	615	685	35
630	11.012.0630.33	630X19,3 SDR33 ISO S-16	8.320	630	19,3	184	89	642	685	35
63	11.012.0063.17	63X3,8 SDR17 ISO S-8	0.107	63	3,8	50	20	75	102	14
75	11.012.0075.17	75X4,5 SDR17 ISO S-8	0.166	75	4,5	50	18	89	122	16
90	11.012.0090.17	90X5,4 SDR17 ISO S-8	0.274	90	5,4	82	40	105	138	17
110	11.012.0110.17	110X6,6 SDR17 ISO S-8	0.350	110	6,6	80	32	125	158	18



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
125	11.012.0125.17	125X7,4 SDR17 ISO S-8	0.343	125	7,4	84	45	132	158	18
140	11.012.0140.17	140X8,3 SDR17 ISO S-8	0.550	140	8,3	92	39	155	188	18
160	11.012.0160.17	160X9,5 SDR17 ISO S-8	0.696	160	9,5	92	40	175	212	18
180	11.012.0180.17	180X10,7 SDR17 ISO S-8	0.687	180	10,7	92	52	183	212	20
200	11.012.0200.17	200X11,9 SDR17 ISO S-8	1.460	200	11,9	110	46	232	268	24
225	11.012.0225.17	225X13,4 SDR17 ISO S-8	1.380	225	13,4	113	60	235	268	24
250	11.012.0250.17	250X14,8 SDR17 ISO S-8	2.440	250	14,8	132	64	285	320	25
280	11.012.0280.17	280X16,6 SDR17 ISO S-8	2.200	280	16,6	128	70	288	320	25
315	11.012.0315.17	315X18,7 SDR17 ISO S-8	3.140	315	18,7	136	68	335	370	25
355	11.012.0355.17	355X21,1 SDR17 ISO S-8	4.480	355	21,1	150	78	373	430	30
400	11.012.0400.17	400X23,7 SDR17 ISO S-8	5.980	400	23,7	155	75	427	482	33
450	11.012.0450.17	450X26,7 SDR17 ISO S-8	11.340	450	26,7	170	73	514	585	46



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
500	11.012.0500.17	500X29,7 SDR17 ISO S-8	10.800	500	29,7	175	79	530	585	46
560	11.012.0560.17	560X33,2 SDR17 ISO S-8	15.760	560	33,2	180	78	615	685	50
630	11.012.0630.17	630X37,4 SDR17 ISO S-8	14.720	630	37,4	180	120	642	685	50
20	11.012.0020.11	20X1,9 SDR11 ISO S-5	0.014	20	1,9	52	30	27	45	7
25	11.012.0025.11	25X2,3 SDR11 ISO S-5	0.027	25	2,3	52	25	33	58	9
32	11.012.0032.11	32X2,9 SDR11 ISO S-5	0.038	32	2,9	50	25	40	68	10
40	11.012.0040.11	40X3,7 SDR11 ISO S-5	0.062	40	3,7	52	24	50	78	11
50	11.012.0050.11	50X4,6 SDR11 ISO S-5	0.085	50	4,6	53	22	61	88	12
63	11.012.0063.11	63X5,8 SDR11 ISO S-5	0.122	63	5,8	50	20	75	102	14
75	11.012.0075.11	75X6,8 SDR11 ISO S-5	0.187	75	6,8	50,5	18	89	122	16
90	11.012.0090.11	90X8,2 SDR11 ISO S-5	0.322	90	8,2	82	40	105	138	17
110	11.012.0110.11	110X10,0 SDR11 ISO S-5	0.425	110	10	82	38	125	158	18



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
125	11.012.0125.11	125X11,4 SDR11 ISO S-5	0.470	125	11,4	82	38	132	158	25
140	11.012.0140.11	140X12,7 SDR11 ISO S-5	0.757	140	12,7	92	37	155	188	25
160	11.012.0160.11	160X14,6 SDR11 ISO S-5	0.960	160	14,6	92	38	175	212	25
180	11.012.0180.11	180X16,4 SDR11 ISO S-5	1.000	180	16,4	93	43	183	212	30
200	11.012.0200.11	200X18,2 SDR11 ISO S-5	2.040	200	18,2	114	40	232	268	32
225	11.012.0225.11	225X20,5 SDR11 ISO S-5	1.960	225	20,5	113	52	235	268	32
250	11.012.0250.11	250X22,7 SDR11 ISO S-5	3.300	250	22,7	130	58	285	320	35
280	11.012.0280.11	280X25,4 SDR11 ISO S-5	3.110	280	25,4	128	66	288	320	35
315	11.012.0315.11	315X28,6 SDR11 ISO S-5	4.600	315	28,6	136	65	335	370	35
355	11.012.0355.11	355X32,2 SDR11 ISO S-5	6.560	355	32,2	150	70	373	430	40
400	11.012.0400.11	400X36,3 SDR11 ISO S-5	8.620	400	36,3	155	70	427	482	46
450	11.012.0450.11	450X40,9 SDR11 ISO S-5	15.360	450	40,9	165	62	514	585	60



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
500	11.012.0500.11	500X45,4 SDR11 ISO S-5	15.100	500	45,4	175	80	530	585	60
630	11.012.0630.11	630X57,2 SDR11 ISO S-5	20.900	630	57,2	175	91,5	642	685	60