



Kısa flanş ANSI enjeksiyon kalıplı Alın kaynaklı PPR gri

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
20	11.012.1020.11	20X1,9 SDR11 ISO S-5	0.015	20	1,9	52	30	27	44,5	7
25	11.012.1025.11	25X2,3 SDR11 ISO S-5	0.024	25	2,3	52	25	33	54,1	9
32	11.012.1032.11	32X2,9 SDR11 ISO S-5	0.036	32	2,9	50	25	40	63,5	10
40	11.012.1040.11	40X3,7 SDR11 ISO S-5	0.051	40	3,7	52	24	50	71,5	11
50	11.012.1050.11	50X4,6 SDR11 ISO S-5	0.076	50	4,6	53	22	61	82,55	12
63	11.012.1063.11	63X5,8 SDR11 ISO S-5	0.117	63	5,8	50	20	75	100,4	14
75	11.012.1075.11	75X6,8 SDR11 ISO S-5	0.172	75	6,8	50,5	18	89	117	16
90	11.012.1090.11	90X8,2 SDR11 ISO S-5	0.303	90	8,2	82	40	105	132,4	17



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	11.012.1110.11	110X10,0 SDR11 ISO S-5	0.439	110	10	82	38	125	158	18
125	11.012.1125.11	125X11,4 SDR11 ISO S-5	0.470	125	11,4	80	38	132	158	25
160	11.012.1160.11	160X14,6 SDR11 ISO S-5	0.960	160	14,6	92	38	175	212	25
200	11.012.1200.11	200X18,2 SDR11 ISO S-5	2.040	200	18,2	114	40	232	268	32
225	11.012.1225.11	225X20,5 SDR11 ISO S-5	1.960	225	20,5	113	52	235	268	32
250	11.012.1250.11	250X22,7 SDR11 ISO S-5	3.320	250	22,7	130	58	285	320	35
315	11.012.1315.11	315X28,6 SDR11 ISO S-5	4.600	315	28,6	136	65	335	370	35
355	11.012.1355.11	355x32,2 SDR11 ISO- S5	6.560	355	32,2	150	70	373	436	40
400	11.012.1400.11	400X36,3 SDR11 ISO S-5	8.620	400	36,3	155	70	427	493	46
450	11.012.1450.11	450X40,9 SDR11 ISO S-5 18"	12.670	450	40,9	165	62	468	545	60