



T segmentli/iç boncuk çıkarılmış
derecelendirme faktörü 0,6 Uçtan
kaynaklı PPH gri

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	z mm	L mm
560	12.326.0560.26	560X21,4 SDR26 ISO S-12,5	46.900	560	21,4	540	1.080
630	12.326.0630.26	630X24,1 SDR26 ISO S-12,5	67.800	630	24,1	615	1.230
710	12.326.0710.26	710X27,2 SDR26 ISO S-12,5	110.000	710	27,2	655	1.310
800	12.326.0800.26	800X30,6 SDR26 ISO S-12,5	149.000	800	30,6	700	1.400
900	12.326.0900.26	900x34,4 SDR26 ISO S-12,5	255.000	1.000	38,2	1.000	2.000
560	12.326.0560.17	560X31,7 SDR17,6 ISO S-8,3	81.500	560	31,7	540	1.080
630	12.326.0630.17	630X35,7 SDR17,6 ISO S-8,3	118.000	630	35,7	615	1.230
710	12.326.0710.17	710X40,2 SDR17,6 ISO S-8,3	159.000	710	40,2	655	1.310
800	12.326.0800.17	800X45,3 SDR17,6 ISO S-8,3	216.000	800	47,4	700	1.400